# Copper valved manifold accessories - ProPEX ball and balancing valves



| Project information            |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

#### Technical data

Material Brass
Subcomponent Material CA 360 Brass
End type 2 Sweat 3/4"
Cold working pressure 249.5 psi


Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar)

180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

Product information and application use

The Uponor ProPEX® Ball and Balance Valve products feature in-line isolation valves.





| Part name   | Part<br>no. | A<br>[inch] | B<br>[inch] | C<br>[inch] | D<br>[inch] | E<br>[inch] | F<br>[inch] | G<br>[inch] | H<br>[inch] | l<br>[inch] | J<br>[inch] |
|---|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|
| ProPEX Ball and Balancing Valve, 5/8" PEX x 3/4" Copper Adapter | Q5906375    | 0.866       | 2.648       | 1.301       | 0.913       | 0.5         | 0.683       | 3.743       | 2.133       | 1           | 4.415       |
| ProPEX Ball and Balancing Valve, 3/4" PEX x 3/4" Copper Adapter | Q5907575    | 0.866       | 2.65        | 1.301       | 0.913       | 0.5         | 0.683       | 3.746       | 2.133       | 1           | 4.417       |

| Part name  | Part no. | Cv  | End Type 1  | Weight per UOM<br>[lbs/UOM] |
|--|----------|-----|-------------|-----------------------------|
| ProPEX Ball and Balancing Valve, 5/8" PEX x 3/4" Copper Adapter    | Q5906375 | 6.6 | ProPEX 5/8" | 0.8                         |
| ProPEX Ball and Balancing Valve, 3/4" PEX x 3/4" Copper<br>Adapter | Q5907575 | 6.7 | ProPEX 3/4" | 0.8                         |

| Part name  | Part no. | Codes | Standards            | Listings |
|--|----------|-------|----------------------|----------|
| Copper valved manifold accessories -<br>ProPEX ball and balancing valves | All      | -     | ASTM F1960 ASTM F877 | -        |

# nstallation Related applications

Install valve according to local building code. Do not dismantle. If soldering, aim flame away from fitting. Remove safety cap. Using Allen key or hex wrench, fully close memory spindle by performing a complete clockwise turn and open it the required number of turns from the closed position. For balancing of manifolds, open the memory spindle fully for the longest loop and balance the other loops by setting their memory spindles according to their loop lengths relative to the longest loop. Refer to the Radiant Floor Installation Handbook for additional information.

### PEX-a Plumbing Systems

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

## Notes

Cv (Q5906375):

6.60

Cv (Q5907575): 6.70

| Footnotes | Contact i              | Contact information     |  |  |  |
|-----------|------------------------|-------------------------|--|--|--|
|           | Uponor Inc.            | Uponor Ltd.             |  |  |  |
|           | 5925 148th Street West | 6510 Kennedy Road       |  |  |  |
| •         | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 |  |  |  |
|           | T 800.321.4739         | T 888.594.7726          |  |  |  |
|           | F 952.891.2008         | F 800.638.9517          |  |  |  |