## υροποι

## ProPEX stainless-steel male threaded adapters


Project mormation	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

l echnical data	
Material	Stainless Steel
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

ProPEX® Stainless Steel Male Threaded Adapters are available for use with reverse osmosis, deionization, and distillation applications producing conditioned water. One end of the adapter is manufactured with the Uponor ProPEX Fitting for connections to Wirsbo AQUAPEX® tubing.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.





Part name	Part no.	Cv	End Type 1	End Type 2
ProPEX Stainless-steel Male Threaded Adapter, 1/2" PEX x 1/2" NPT	Q8525050	5	ProPEX 1/2"	MNPT 1/2"
ProPEX Stainless-steel Male Threaded Adapter, 3/4" PEX x 3/4" NPT	Q8527575	11.3	ProPEX 3/4"	MNPT 3/4"
ProPEX Stainless-steel Male Threaded Adapter, 1" PEX x 1" NPT	Q8521010	19.9	ProPEX 1"	MNPT 1"

Part name	Part no.	Codes	Standards	Listings	
ProPEX stainless-steel male threaded adapters	All	UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	ASTM F1960 CSA B137.5	HUD MR 1269 ICC-ES-PMG cNSFus- pw IAPMO 3558 U.P.Code	
In addition, the following parts have	In addition, the following parts have additional codes, standards, or listings:				
ProPEX Stainless-steel Male Threaded Adapter, 1/2" PEX x 1/2" NPT	Q8525050		NSF-61		
ProPEX Stainless-steel Male Threaded Adapter, 3/4" PEX x 3/4" NPT	Q8527575		NSF-61		
ProPEX Stainless-steel Male Threaded Adapter, 1" PEX x 1" NPT	Q8521010		NSF/ANSI/CAN 61		

Installation	Related applications
Use the appropriate ProPEX Ring for the tubing. For more information, refer to the AQUAPEX Professional Plumbing Installation Handbook or Uponor Radiant Floor Installation Handbook.	PEX-a Plumbing Systems

Contact information		
Uponor Inc.	Uponor Ltd.	
5925 148th Street West	6510 Kennedy Road	
Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
T 800.321.4739	T 888.594.7726	
F 952.891.2008	F 800.638.9517	
	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739	