
Uponor PP-RCT mechanical pipes, SDR 9 with fiber

Project information Job name: Location: Engineer: Date submitted: Contractor: Submitted by: Manufacturer's representative: Approved by:

| Technical data | | | |
|-------------------------|--------------------------------------|--|--|
| Material | PP-RCT | | |
| Temp/pressure ratings | 73 °F (23 °C) at 270 psi (18.6 bar) | | |
| | 120 °F (49 °C) at 176 psi (12.1 bar) | | |
| | 180 °F (82 °C) at 100 psi (6.9 bar) | | |
| Prop 65 label required? | No | | |

Product information and application use

Use Uponor PP-RCT mechanical pipe to convey fluid for hydronic heating and cooling or industrial applications. The pipe contains a fiber layer coextruded into the mid-wall of the pipe to reduce expansion/contraction with temperature changes.



Uponor

| Part name | Part no. | R value |
|---|------------|---------|
| 1" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 13-ft. straight length | PR9231310 | 0.1 |
| 1 1/4" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 13-ft. straight length | PR9231313 | 0.12 |
| 1 1/2" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 13-ft. straight length | PR9231315 | 0.15 |
| 2" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 13-ft. straight length | PR9231320 | 0.19 |
| 2 1/2" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 19-ft. straight length | PR9231925 | 0.23 |
| 3" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 19-ft. straight length | PR9231930 | 0.27 |
| 4" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 19-ft. straight length | PR9231940 | 0.38 |
| 6" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 19-ft. straight length | PR9231960 | 0.48 |
| 8" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 19-ft. straight length | PR9231980 | 0.6 |
| 10" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 19- ft. straight length | PR92319100 | 0.75 |
| 12" Uponor PP-RCT Mechanical Pipe, SDR 9 with Fiber, 19- ft. straight length | PR92319120 | 0.94 |

| Part name | Part no. | Codes | Standards | Listings |
|---|----------|-------------|--|--|
| Uponor PP-RCT mechanical pipes, SDR 9 with fiber | All | CMCIIMCIUMC | ASTM E84 NSF/ANSI 14 ASTM F2389 CSA B137.11 | ICC-ES-PMG 1106 IAPMO-R&T 8358 QAI P321-5 IAPMO K-12775 |

| Installation | Related applications |
|--|--------------------------------------|
| Use approved butt-fusion or socket-fusion connection methods. Refer to the Uponor PP-RCT | Hydronic heating and cooling systems |
| manual for complete details. | Industrial |

| Footnotes | Contact information | |
|-----------|------------------------|-------------------------|
| | Uponor Inc. | Uponor Ltd. |
| | 5925 148th Street West | 6510 Kennedy Road |
| - | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 |
| | T 800.321.4739 | T 888.594.7726 |
| | F 952.891.2008 | F 800.638.9517 |