# Copper valved manifolds with ProPEX ball valves

## Project information

| | |
|---|---|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

## Technical data

| | |
|---|---|
| Material | Copper |
| Manifold size | 2 inch |
| Loop Cv | 7.3 Cv |
| End type 1 | ProPEX 3/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar)<br>210 °F (99 °C) at 149 psi (10.3 bar) |
| Max. fluid flow rate | 45 gpm |
| Prop 65 label required? | Yes |



## Product information and application use

The 2" Copper Valved Manifold with ProPEX® Ball Valves is used for radiant heating projects. The manifold has a 2" copper sweat fitting adapter supply connection and ¾" nominal branches. This 12-outlet manifold is preassembled with ⅝" or ¾" ProPEX ball valve connections.

*This product is made to order, please contact customer service for lead time.*

| Part name | Part no. | A [inch] | B [inch] | C [inch] | Weight per UOM [lbs/UOM] |
|---|---|---|---|---|---|
| 2" x 4' Copper Valved Manifold with 3/4" ProPEX Ball Valves, 12 outlets | Q2811275 | 48 | 6.228 | 2.319 | 15.5 |

| Part name | Part no. | Codes | Standards | Listings |
|---|---|---|---|---|
| Copper valved manifolds with ProPEX ball valves | Q2811275 | - | CSA B137.5\|ASTM F877 | cNSFus-rfh |

## Installation

Any product designed to mount 2" copper pipe may be used as a mounting bracket. Refer to the Uponor Radiant Installation Handbook for additional information. Accessories: 2" Copper Manifold End Cap (A2402000).

## Related applications

Radiant Heating and Cooling Systems

## Notes

Ball Valve Cv:
" outlet - 7.00
¾" outlet - 7.30

## Footnotes

-

## Contact information


Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517


© 2026 Uponor North America. All Rights Reserved