

Copper valved manifolds with R20/R25 threaded ball valves

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Cv	7
Material	Copper
Manifold size	2 inch
End type 1	ISO 228-G 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar)
Max. fluid flow rate	45 gpm
Prop 65 label required?	Yes



Product information and application use

The 2" x 4' Copper Valved Manifold with R20/R25 Threaded Ball Valves is designed for radiant heating applications. The manifold has a 2" copper sweat fitting adapter supply connection and 3/4" nominal branches that are 4 inches on center. This 12-outlet manifold comes preassembled with R20 and R25 threaded ball valve connections.

This product is made to order, please contact [customer service](#) for lead time.

Part name	Part no.	A [inch]	B [inch]	C [inch]	Weight per UOM [lbs/UOM]
2" x 4' Copper Valved Manifold with R20 Threaded Ball Valves, 12 outlets	F2811220	48	5.728	2.319	14.75

Part name	Part no.	Codes	Standards	Listings
Copper valved manifolds with R20/R25 threaded ball valves	F2811220	-	CSA B125 CSA B137.5 ASTM F877	cNSFus-rfh

Installation

Install using any product designed to mount 2" copper pipe as a mounting bracket. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.

Related applications

Radiant Heating and Cooling Systems
Permafrost Protection Systems
Turf Conditioning Systems

Notes

Ball Cv for the R20 outlet:

7.00

Ball Cv for the R25 outlet: 7.30

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517