PEX stand-up brackets

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	Plastic
Subcomponent Material	PVC
Prop 65 label required?	Yes

Product information and application use

Use the PEX Stand-up Bracket in residential slab or commercial multi-floor construction. The brackets are available in either single-tube or five-tube configurations. The bracket supports up to 1" Uponor hePEX™ plus or Uponor AQUAPEX® tubing, or a 1" utility-grade, polyethylene sleeving.



Part name	Part no.	Weight per UOM [lbs/UOM]
Single-tube PEX Stand-up Bracket for 1/2" PEX	F5801000	0.5
Five-tube PEX Stand-up Bracket for 1/2" PEX	F5805000	1.1

Installation

Screw or nail the ¾" fastening tab to the floor or concrete forms. Secure the brackets to the deck form. Then install the ½" PEX tubing in the brackets, either with the ½" PEX tubing alone or with the ½" PEX tubing sleeved inside corrugated polyethylene carrier tube. Wire the tube at the top of bracket to bracket at the wiring tab.

Related applications

PEX-a Plumbing Systems

Radiant Floor Heating and Cooling Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726

© 2026 Uponor North America. All Rights Reserved