

ProPEX EP plugs

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-----------------------|-------------------------------------|
| Material | Engineered Polymer |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |

Product information and application use

ProPEX® engineered polymer (EP) plugs terminate Uponor crosslinked polyethylene (PEX-a) tubing ends and are available for use in hot and cold domestic potable water systems, residential fire sprinkler systems and hydronic heating and cooling systems.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | End Type 1 | Weight per UOM [lbs/UOM] |
|-------------------------------|----------|----------|----------|----------|----------|---------------|--------------------------|
| ProPEX EP Plug for 1/2" PEX | Q4350500 | 0.844 | 0.8 | 0.65 | 0.719 | ProPEX 1/2" | 0.01 |
| ProPEX EP Plug for 3/4" PEX | Q4350750 | 1.084 | 1.22 | 0.95 | 0.959 | ProPEX 3/4" | 0.01 |
| ProPEX EP Plug for 1" PEX | Q4351000 | 1.316 | 1.35 | 1.35 | 1.191 | ProPEX 1" | 0.02 |
| ProPEX EP Plug for 1 1/4" PEX | Q4351250 | 1.645 | 1.74 | 1.74 | 1.445 | ProPEX 1-1/4" | 0.04 |
| ProPEX EP Plug for 1 1/2" PEX | Q4351500 | 1.914 | 2.06 | 2.06 | 1.714 | ProPEX 1-1/2" | 0.07 |
| ProPEX EP Plug for 2" PEX | Q4352000 | 2.357 | 2.7 | 2.157 | 2.16 | ProPEX 2" | 0.16 |

| Part name | Part no. | Codes | Standards | Listings |
|---|----------|--|--|---|
| ProPEX EP plugs | All | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | ASTM E814 ULC S115 ASTM F877 ASTM F1960 CSA B137.5 ULC S102.2 ASTM E1119 UL 263 ULC S101 | IAPMO-ES HUD MR 1269 ICC-ES-PMG UL U.P.Code cQAlus P321 |
| In addition, the following parts have additional codes, standards, or listings: | | | | |
| ProPEX EP Plug for 1/2" PEX | Q4350500 | | NSF/ANSI/CAN 61 NSF/ANSI 14 | cNSFus-pw |
| ProPEX EP Plug for 3/4" PEX | Q4350750 | | UL 1821 NSF-61 NSF-14 | cNSFus-pw-fs |
| ProPEX EP Plug for 1" PEX | Q4351000 | | UL 1821 NSF-61 NSF-14 | cNSFus-pw-fs |
| ProPEX EP Plug for 1 1/4" PEX | Q4351250 | | UL 1821 NSF-61 NSF-14 | cNSFus-pw-fs |
| ProPEX EP Plug for 1 1/2" PEX | Q4351500 | | NSF-61 NSF-14 | cNSFus-pw |
| ProPEX EP Plug for 2" PEX | Q4352000 | | NSF/ANSI/CAN 61 NSF/ANSI 14 | cNSFus-pw |

Installation

Related applications

Note: ProPEX tool is required. ProPEX rings sold separately.

- PEX-a Plumbing Systems
- Hydronic Radiant Heating and Cooling Systems
- Turf Conditioning Systems
- Permafrost Prevention Systems
- AquaSAFE™ Fire Safety Systems

Footnotes

Contact information

| | | |
|---|---|---|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 | Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |
|---|---|---|