

## ProPEX lead-free (LF) brass ice maker boxes

| Project information            |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

## Technical data

Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar)

180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

## Product information and application use

The ProPEX® Ice Maker Box with Support Brackets,  $\frac{1}{2}$ " (LF Brass) Valve with snap-in frame includes a  $\frac{1}{2}$ " lead-free brass valve with  $\frac{1}{2}$ " O.D. compression connection. This high-impact box is an aesthetic, convenient option for connecting to standard ice maker tubing. Two support brackets are provided for easy mounting.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name                      |                                       | Part no.  | A<br>[inch] | B<br>[inch] | C<br>[inch] | Material<br>group  | End<br>Type 1 | End Type<br>2 | Prop 65<br>label<br>required? | Weight<br>per UOM<br>[lbs/UOM] |
|--------------------------------|---------------------------------------|-----------|-------------|-------------|-------------|--------------------|---------------|---------------|-------------------------------|--------------------------------|
| ProPEX Ice Make<br>Brass Valve | er Box with Support Brackets, 1/2" LF | LF5955025 | 20.29       | 6           | 3.55        | -                  | ProPEX        | Compression   | Yes                           | 0.87                           |
| 1/4" Insert (stainle           | ess steel)                            | F5400250  | 0.719       | 0.323       | 0.323       | Stainless<br>Steel | -             | -             | -                             | 0                              |

| Part name                                   | Part no. | Codes                 | Standards   | Listings             |
|---|----------|-----------------------|---|----------------------|
| ProPEX lead-free (LF) brass ice maker boxes | All      | UPC IPC NPC of Canada | NSF-372 ASME A112.18.1 ASTM<br>F877 ASTM F1960 CSA B125 CSA<br>B137.5 NSF-61 NSF-14 | cNSFus-pw-G U.P.Code |

Installation Related applications

Mount in wall cavity at the desired location (e.g., behind refrigerator) using the supplied mounting brackets or directly to studs. For more information, refer to the AquaPEX® Professional Plumbing Installation Guide.

PEX-a Plumbing Systems

| Footnotes | Contact is             | Contact information     |  |  |  |
|-----------|------------------------|-------------------------|--|--|--|
|           | Uponor Inc.            | Uponor Ltd.             |  |  |  |
|           | 5925 148th Street West | 6510 Kennedy Road       |  |  |  |
| -         | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 |  |  |  |
|           | T 800.321.4739         | T 888.594.7726          |  |  |  |
|           | F 952.891.2008         | F 800.638.9517          |  |  |  |