

# QS-style coupling nipples

## Project Information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

## Technical data

Material	Brass
End type 1	ISO 228-G 3/4"
End type 2	ISO 228-G 3/4"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

## Product information and application use

The Uponor QS-style Coupling Nipple is available in R20 and R25 thread. It is used with compression fittings to connect 5/16", 3/8", 1/2", 5/8" or 3/4" Wirsbo hePEX™ pipe in radiant heating and cooling applications. Note that R25 is for 5/8" and 3/4" pipe only.



Part name	Part no.	A [Inch]	B [Inch]	C [Inch]	Weight per UOM [lbs/UOM]
QS-style Coupling Nipple, R20 x R20	A4322020	1.299	1.227	1.063	0.17

Part name	Part no.	Codes	Standards	Listings
QS-style coupling nipples	A4322020	-	ASTM F877 R20: ISO 228-G 3/4"	-

## Installation

Corresponding QS-style fitting assembly threads onto QS-style Coupling Nipple fitting for repairs. For more information, refer to the Uponor Radiant Installation Handbook.

## Related applications

Radiant Heating and Cooling Systems

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517