

Slab sensor 10k

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

Slab sensors read temperature conditions to provide feedback and information to temperature control devices



Part name	Part no.	Weight per UOM [lbs/UOM]
Slab Sensor, 10k	A9010599	0.3

Installation	Related applications
Fasten the terminal connectors on the back of the thermostat. For more information, refer to the manuals for the Uponor Heat-only Thermostat with Touchscreen (A3100101) and the Uponor Wireless Digital Thermostat (A3800167)	<ul style="list-style-type: none"> Radiant heating systems Permafrost Protection Systems Turf Conditioning Systems

Codes	Standards	Listings
-	-	-

Notes

Ambient conditions:
 10% to 90% humidity (non-condensing)
 Sensor type: 10k J-curve
 Tolerance: +/- 1% at 77°F (25°C)
 Wire type: 22 gauge
 IP68 continuous immersion 3m /10 ft

Footnotes	Contact information		
-	<table border="0"> <tr> <td> Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 </td> <td> Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 </td> </tr> </table>	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517		