Uponor PP-RCT reducing tees, cold potable (butt fusion)

Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Temp/pressure ratings	73 °F (23 °C) at 215 psi (14.48 bar) 140 °F (60 °C) at 120 psi (8.3 bar) 180 °F (82 °C) at 80 psi (5.5 bar)

Product information and application use

Use Uponor PP-RCT cold potable reducing tees with Uponor PP-RCT cold potable pipe to convey water for cold potable plumbing applications as well as other lower-pressure, lower-temperature applications.



Part name	Part no.	End Type 1	End Type 2	End Type 3	Material group
Uponor PP-RCT Reducing Tee, Cold Potable, 6" x 6" x 4", SDR 11	PR114756640	Butt 6"	Butt 6"	Butt 4"	-
Uponor PP-RCT Reducing Tee, Cold Potable, 8" x 8" x 4", SDR 11	PR114758840	Butt 8"	Butt 8"	Butt 4"	PP-RCT
Uponor PP-RCT Reducing Tee, Cold Potable, 8" x 8" x 6", SDR 11	PR114758860	Butt 8"	Butt 8"	Butt 6"	PP-RCT

Part name	Part no.	Codes	Standards	Listings
Uponor PP-RCT reducing tees, cold potable (butt fusion)	All	UPC|IRC|IPC|NPC of Canada|UMC|CMC|CPC|IMC	NSF/ANSI/CAN 61|ASTM E84|NSF/ANSI 14|NSF/ANSI 51|ASTM F2389|CSA B137.11	ICC-ES-PMG 1106|IAPMO-R&T 8358|QAI P321-5|IAPMO K-12775

Installation

Use approved butt-fusion connection methods. Refer to the Uponor PP-RCT manual for complete details.

Related applications

Domestic water systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved