Uponor PP-RCT 90 elbows, cold potable (butt fusion)

Uponor

r reject internation			
Job name:		Location:	
Engineer:		Date submitted:	
Contractor:		Submitted by:	
Manufacturer's representative:		Approved by:	
Technical data			
Material Temp/pressure ratings	PP-RCT 73 °F (23 °C) at 215 psi (14.48 bar) 140 °F (60 °C) at 120 psi (8.3 bar) 180 °F (82 °C) at 80 psi (5.5 bar)	A	
Product information and app	lication use		
	otable 90 elbows with Uponor PP-RCT cold potable pipe to convey water plications as well as other lower-pressure, lower-temperature		

Part name	Part no.	End Type 1	End Type 2
Uponor PP-RCT 90 Elbow, Cold Potable, 6" x 6", SDR 11	PR114769060	Butt 6"	Butt 6"
Uponor PP-RCT 90 Elbow, Cold Potable, 8" x 8", SDR 11	PR114769080	Butt 8"	Butt 8"

Part name	Part no.	Codes	Standards	Listings
Uponor PP-RCT 90 elbows, cold potable (butt fusion)	All	UPC IRC IPC NPC of Canada UMC CMC CPC IMC	NSF/ANSI/CAN 61 ASTM E84 NSF/ANSI 14 ASTM F2389 CSA B137.11	ICC-ES-PMG 1106 IAPMO-R&T 8358 QAI P321-5 IAPMO K-12775

-

Related applications

Installation

Use approved butt-fusion connection methods. Refer to the Uponor PP-RCT manual for complete details.

Footnotes	Contact	Contact information	
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.638.9517	