

TotalFit male threaded adapters

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |

Technical data


Material Engineered Polymer
Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar)


180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? No

Product information and application use

TotalFit™ is the professional-grade engineered polymer (EP) push-to-connect solution that provides greater value for residential projects with the same versatility and speed as brass push-to-connect fittings for PEX, PE-RT, CPVC, and copper piping systems.





| Part name | Part no. | End Type 1 | End Type 2 |
|---|-----------|---------------|------------|
| TotalFit Male Threaded Adapter, 1" x 1" NPT | TF4521010 | TotalFit 1" | MNPT 1" |
| TotalFit Male Threaded Adapter, 1/2" x 1/2" NPT | TF4525050 | TotalFit 1/2" | MNPT 1/2" |
| TotalFit Male Threaded Adapter, 1/2" x 3/4" NPT | TF4525075 | TotalFit 1/2" | MNPT 3/4" |
| TotalFit Male Threaded Adapter, 3/4" x 1" NPT | TF4527510 | TotalFit 3/4" | MNPT 1" |
| TotalFit Male Threaded Adapter, 3/4" x 3/4" NPT | TF4527575 | TotalFit 3/4" | MNPT 3/4" |

| Part name | Part no. | Codes | Standards | Listings |
|---------------------------------|----------|---|--|---|
| TotalFit male threaded adapters | All | UPC IRC IPC NPC of Canada UMC CMC CPC IMC | ASTM F877 NSF/ANSI/CAN 372 NSF/ANSI/CAN 61 NSF/ANSI 14 ASSE 1061 | IAPMO K-13573 IAPMO K- 13571 IAPMO K-13572 |

In addition, the following parts have additional codes, standards, or listings:

TotalFit Male Threaded Adapter, 3/4"

x 3/4" NPT

TF4527575

Installation Related applications

Install on PEX, PE-RT, CPVC, and copper piping systems. Use deburr and depth tool to remove excess material or burrs and mark the appropriate depth on pipe. If using flexible PEX or PE-RT, install the insert inside the pipe first before making the connection. Only use PTFE thread seal tape (with a minimum of three wraps) to seal male and female adapters. Refer to the Uponor TotalFit Instruction Sheet for additional information.

Plumbing

Hydronic Heating & Cooling

| | Footnotes | Contact in | Contact information | | |
|---|-----------|------------------------|-------------------------|--|--|
| | | Uponor Inc. | Uponor Ltd. | | |
| | | 5925 148th Street West | 6510 Kennedy Road | | |
| - | | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | |
| | | T 800.321.4739 | T 888.594.7726 | | |
| | | F 952.891.2008 | F 800.638.9517 | | |