TotalFit removal tools

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Product information and application use

TotalFit™ is the professional-grade engineered polymer (EP) push-to-connect solution that provides greater value for residential projects with the same versatility and speed as brass push-to-connect fittings for PEX, PE-RT, CPVC, and copper piping systems.



	Part name	Part no.	Prop 65 label required?
✔	TotalFit Removal Tool, 1/2	TF4800500	No
	TotalFit Removal Tool, 3/4	TF4800750	No
	TotalFit Removal Tool, 1	TF4801000	-

Part name	Part no.	Codes	Standards	Listings
TotalFit removal tools	All	UPC|IRC|IPC|NPC of Canada|UMC|CMC|CPC|IMC	NSF-372|ASTM F877|NSF-61|NSF-14|ASSE 1061	-

Installation

Use to remove TotalFit connections from Install on PEX, PE-RT, CPVC, and copper piping systems.

1. Attach the appropriately sized removal tool to the pipe
2. Press it back against the release collar of the fitting. This will disengage the grab ring.
3. Remove the pipe from the fitting.

Refer to the Uponor TotalFit Instruction Sheet for additional information.

Related applications

Plumbing

Hydronic Heating & Cooling

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved