## Lead

d-free (LF) brass compression straight stop v	alves Uponor
formation	
:	Location:
	Date submitted:
r.	Submitted by:
Jrer's representative:	Approved by:

Manufacturer's representative:


Project info Job name: Engineer: Contractor:


Technical data LF Brass Material End type 1 Compression 1/2" . UNEF 3/8" End type 2 Temp/pressure ratings 194 °F (90 °C) at 145 psi (10 bar) Prop 65 label required? Yes

## Product information and application use

For point-of-use shutoff at the fixture, compression straight and angle stop valves are lead-free (LF) brass, chrome-plated, quarter-turn ball valves that include a Teflon®-coated brass compression ring and a stainless-steel insert for compression connection to 1/2" Uponor AquaPEX® pipe and a 3/8" male threaded connection for fixture risers.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding applicationspecific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.





Part name	Part no.	Codes	Standards	Listings
Lead-free (LF) brass compression straight stop valves	LF5425038	UPC IBC IRC IPC NPC of Canada UMC NSPC IMC	ASME A112.18.1 NSF/ANSI/CAN 372 ASTM F877 ASTM F1960 CSA B125 CSA B137.5 NSF/ANSI/CAN 61 NSF/ANSI 14	cNSFus-pw-G U.P.Code

Installation	Related applications
Install valves according to local building code. Use only the Teflon®-coated brass compression rings and stainless-steel inserts supplied by Uponor with these compression stop valves. Substitution can result in valve connection failure. Do not dismantle. Refer to the Uponor PEX Piping Systems Design and Installation Manual or Uponor PEX Piping Systems Installation Guide for additional information. For rigid fixture riser connections, use the Uponor %" OD Compression Nut and Nylon Sleeve (part number F5440380), sold separately.	PEX-a Plumbing Systems

Footnotes	Contact information		
	Uponor Inc.	Uponor Ltd.	
	5925 148th Street West	6510 Kennedy Road	
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
	T 800.321.4739	T 888.594.7726	
	F 952.891.2008	F 800.638.9517	