Product data sheet



1/2" Uponor AquaPEX White, 100-ft. coil

F1040500

Use Uponor AquaPEX® white pipe in domestic hot, cold, and hot-water recirculation systems as well as AquaSAFE™ residential fire safety systems. The pipe is available in sizes from ¼" to 3" in various coil lengths. It is also suitable for use in hydronic heating and/or cooling applications where the system contains no ferrous corrodible components or where any ferrous components are isolated from the pipe.

For use in residential fire safety systems, refer to Uponor AquaPEX white coils for residential fire sprinkler systems.

1/2" Uponor AquaPEX White, 100-ft. coil

F1040500

Dimensions

Inner diameter coil [inch]	15.75 inch
Inner diameter coil [mm]	400.05 mm
Outer diameter coil [inch]	23.5 inch
Outer diameter coil [mm]	596.9 mm
Coil width [inch]	3.5 inch
Inner diameter pipe [inch]	0.475 inch
Inner diameter pipe [mm]	12.07 mm
Outer diameter pipe [inch]	0.625 inch
Outer diameter pipe [mm]	15.88 mm
Weight per UOM [lbs/UOM]	6 lbs/uom
Weight per UOM [kg/UOM]	2.722 kg/uom

Technical Data

Material group	PEX
Operating Temperature 1 [°F]	73 °F
Operating Temperature 2 [°F]	180 °F
Operating Temperature 3 [°F]	200 °F

Excellence in Flow

Visit our webpage to get in contact with your local specialist:
www.georgfischer.com/locations



Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E communications@georgfischer.com

www.uponor.com

+GF+