

Ecoflex potable PEX twin coils

Project information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Material	PEX
Subcomponent Material	Jacket: Corrugated, seamless high-density polyethylene (HDPE); UV-protected
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)



Product information and application use

Ecoflex® Potable PEX Twin features two Uponor AquaPEX® service pipes protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use Ecoflex Potable PEX Twin for hot and cold potablewater applications. Join pipes using Uponor ProPEX® or WIPEXTM fittings.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

Part name	Part no.	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	R value	Weight per UOM [lbs/UOM]
1" Potable PEX Twin with 6.9" Jacket, 600-ft. coil	5226910	6.9	12	6.9	0.862	1.125	11.3	1.3
1 1/4" Potable PEX Twin with 6.9" Jacket, 500-ft. coil	5226913	6.9	12	6.9	1.054	1.375	9.5	1.4
1 1/2" Potable PEX Twin with 6.9" Jacket, 300-ft. coil	5226915	6.9	12	6.9	1.244	1.625	7.7	1.55
2" Potable PEX Twin with 7.9" Jacket, 300-ft. coil	5227920	7.9	12	7.9	1.629	2.125	6.5	2.68

Part name	Part no.	Codes	Standards	Listings
Ecoflex potable PEX twin coils	All	UPC IPC NPC of Canada NSPC	ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 ASTM F2023 ASTM F877	U.P.Code

Installation	Related applications
Install Ecoflex Potable PEX in hot or cold potable-water applications. Join pipes using Uponor ProPEX®. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For additional information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.	Pre-Insulated Pipe Systems Permafrost Prevention Systems Plumbing Systems AquaSAFE™ Fire Safety Systems

Footnotes	Contact information
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517