

Two-wire thermal actuators for EP Heating Manifolds

Project information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Two-wire Thermal Actuators are slow-opening thermal actuators that mount directly onto Uponor manifolds. They provide individual-loop flow control on multi-zoned manifolds.



| Part name  | Part no. | A [inch] | B [inch] | C [inch] | Current draw max. [A] | Operating voltage AC [VAC] | Weight per UOM [lbs/UOM] |
|--|----------|----------|----------|----------|-----------------------|----------------------------|--------------------------|
| Two-wire Thermal Actuator for EP Heating Manifolds | A3030522 | 2.42     | 1.56     | 1.56     | 0.083                 | 24                         | 0.26                     |

| Part name   | Part no. | Codes | Standards       | Listings |
|---|----------|-------|-----------------|----------|
| Two-wire thermal actuators for EP Heating Manifolds | A3030522 | -     | Class II wiring | -        |

Installation

Related applications

Mount directly onto the manifold. Refer to the manifold installation guide for detailed instructions.

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

Time to Open/Close:  
3 to 5 minutes

Footnotes

Contact information

|   |   |   |
|---|---|---|
| - | Uponor Inc.<br>5925 148th Street West<br>Apple Valley, MN 55124<br>T 800.321.4739<br>F 952.891.2008 | Uponor Ltd.<br>6510 Kennedy Road<br>Mississauga, ON L5T 2X4<br>T 888.594.7726<br>F 800.638.9517 |
|---|---|---|