

ProPEX lead-free (LF) brass fire sprinkler accessories

Project information

Job name :	Location :
Engineer :	Date submitted:
Contractor :	Submitted by:
Manufacturer's representative :	Approved by :

Technical data

End type 1	ProPEX 1/2"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

Uponor fire sprinkler accessories include the following options sold separately: Fire sprinkler adapter mounting brackets, Fire sprinkler adapter push-on nut (25/package) and Screws. Screws #10 X 1 1/2" pan head, full thread (100/package).



Part name	Part no.	A [Inch]	B [Inch]	C [Inch]	Weight per UOM [lbs/UOM]	Equivalent length branch [ft]	Material group
Fire Sprinkler Adapter Mounting Bracket, 3/4" and 1	A7750700	3.171	2.484	1.839	0.17	-	-
Fire Sprinkler Adapter Push-on Nut, 25/pkg.	F7000005	2.125	0.233	2.125	0.01	0	-
Screws, #10 x 1 1/2", Pan Head, Full Thread, 100/pkg.	F7001500	-	-	-	-	-	-

Installation

N/A

Related applications

AquaSAFE™ Fire Safety Systems

Codes

-

Standards

UL 1821

Listings

-

Trademark information

ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.636.9517