υροποι

PEX-a pipe supports

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with uninsulated Uponor AquaPEX® or Wirsbo hePEX[™] PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



Part name	Part no.	A [inch]	B [inch]	C [inch]	Material group	Subcomponent Material	Prop 65 label required?	Weight per UOM [lbs/UOM]
1/2" PEX-a Pipe Support, 9-ft. length	F7040500	108	0.677	0.406	Metal	Commercial- grade (Type B) galvanized steel	-	1.1
3/4" PEX-a Pipe Support, 9-ft. length	F7040750	108	0.921	0.552	Metal	Commercial- grade (Type B) galvanized steel	No	1.5
1" PEX-a Pipe Support, 9-ft. length	F7041000	108	1.163	0.698	Metal	Commercial- grade (Type B) galvanized steel	-	1.91
1 1/4" PEX-a Pipe Support, 9-ft. length	F7041250	108	1.396	0.837	Metal	Commercial- grade (Type B) galvanized steel	-	2.1
1 1/2" PEX-a Pipe Support, 9-ft. length	F7041500	108	1.623	0.973	Metal	Commercial- grade (Type B) galvanized steel	-	2.5
2" PEX-a Pipe Support, 9-ft. length	F7042000	108	2.095	1.256	Metal	Commercial- grade (Type B) galvanized steel	-	3.6
2 1/2" PEX-a Pipe Support, 9-ft. length	F7042500	108	2.562	1.537	Metal	Commercial- grade (Type B) galvanized steel	-	4.6
PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX	Q7410510	-	-	-	Plastic	-	-	0
3" PEX-a Pipe Support, 9-ft. length	F7043000	108	3.024	1.81	Metal	Commercial- grade (Type B) galvanized steel	-	6.2
PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX	Q7411220	-	-	-	Plastic	-	-	0.01
PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX	Q7412540	-	-	-	Plastic	-	-	0.01

Part name	Part no.	Codes	Standards	Listings	
PEX-a pipe supports	All	IMC UMC	ASTM E84	QAI P321 (up to 3")	
Installation	Related applications				
			PEX-a Plumbing Systems		
Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.		- Radian	Radiant Heating and Cooling Systems		
		•	AquaSAFE™ Fire Safety Systems		

Footnotes	Contact in	formation
	Uponor Inc.	Uponor Ltd.
	5925 148th Street West	6510 Kennedy Road
·	Apple Valley, MN 55124	Mississauga, ON L5T 2X4
	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.638.9517