## ProPEX lead-free (LF) brass fire sprinkler adapter tees

| Flojoumonnauon                 |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |
|                                |                 |

| l echnical data         |                                     |
|-------------------------|-------------------------------------|
| Material                | LF Brass                            |
| End type 3              | FNPT 1/2"                           |
| Temp/pressure ratings   | 73 °F (23 °C) at 160 psi (11 bar)   |
|                         | 180 °F (82 °C) at 100 psi (6.9 bar) |
|                         | 200 °F (93 °C) at 80 psi (5.5 bar)  |
| Prop 65 label required? | Yes                                 |

## Prop 65 label required? Yes Product information and application use

Designed for use with <sup>3</sup>/<sub>4</sub>" or 1<sup>\*</sup> Uponor AquaPEX® tubing, the ProPEX® Lead-free Brass Fire Sprinkler Adapter Tee connects fire sprinklers to the Uponor residential AquaSAFE™ Looped multipurpose fire safety system, which combines fire sprinklers with a home's potable cold-water plumbing system. Use Uponor ProPEX fittings for the connections.



uponor

| Part name   | Part no.  | A<br>[inch] | B<br>[inch] | C<br>[inch] | D<br>[inch] | E<br>[inch] | F<br>[inch] | G<br>[inch] | H<br>[inch] | l<br>[inch] | End<br>Type<br>1 |
|---|-----------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|------------------|
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 3/4" PEX x 3/4" PEX x 1/2" FNPT | LF7707575 | 0.945       | 0.865       | 0.865       | 0.945       | 0.56        | 1.089       | 3.62        | 2.209       | 1.46        | ProPEX<br>3/4"   |
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 1" PEX x<br>1" PEX x 1/2" FNPT  | LF7701010 | 1.181       | 0.865       | 0.865       | 1.181       | 0.56        | 1.089       | 4.092       | 2.209       | 1.46        | ProPEX<br>1"     |

| Part name  | Part no.  | End Type 2  | Weight per UOM [lbs/UOM] |
|--|-----------|-------------|--------------------------|
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 3/4" PEX x 3/4"<br>PEX x 1/2" FNPT | LF7707575 | ProPEX 3/4" | 0.62                     |
| ProPEX LF Brass Fire Sprinkler Adapter Tee, 1" PEX x 1"<br>PEX x 1/2" FNPT     | LF7701010 | ProPEX 1"   | 0.62                     |

| Part name   | Part no. | Codes   | Standards  | Listings                               |
|---|----------|---|--|--|
| ProPEX lead-free (LF) brass fire sprinkler adapter tees | Ali      | UPC IBC IRC IPC NPC of<br>Canada UMC NSPC IMC | NSF-372 ASTM F877 ASTM<br>F1960 CSA B137.5 UL 1821 NSF-<br>61 NSF-14 | cNSFus-pw-fs-G ICC-ES-<br>PMG U.P.Code |

| Installation  | Related applications                                    |  |  |
|---|---|--|--|
| Use the appropriate Uponor ProPEX Ring for the tubing. Install the tee using the Fire Sprinkler<br>Adapter Mounting Bracket (A7750700) and Fire Sprinkler Adapter Push-on Nut (F7000005). For<br>more information, refer to the Uponor AquaSAFE Looped System Installation Guide. | PEX-a Plumbing Systems<br>AquaSAFE™ Fire Safety Systems |  |  |
| Footnotes   | Contact information                                     |  |  |
| Foothotes   | Contact information                                     |  |  |

| Uponor Inc.            | Uponor Ltd.             |
|------------------------|-------------------------|
| 5925 148th Street West | 6510 Kennedy Road       |
| Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 |
| T 800.321.4739         | T 888.594.7726          |
| F 952.891.2008         | F 800.638.9517          |
|                        |                         |