

EP branch multi-port tees

Project information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

Technical data

|                       |                                     |
|-----------------------|-------------------------------------|
| Material              | Engineered Polymer                  |
| End type 2            | ProPEX 1/2"                         |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)   |
|                       | 180 °F (82 °C) at 100 psi (6.9 bar) |
|                       | 200 °F (93 °C) at 80 psi (5.5 bar)  |

Product information and application use

Engineered polymer (EP) branch multi-port tees are used in hot and cold domestic potable water distribution systems. The multi-port tees are available with 3/4" or 1" ProPEX® inlets and 1/2" ProPEX outlets.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name                                       | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | End Type 1  | Weight per UOM [lbs/UOM] |
|---|----------|----------|----------|----------|----------|----------|----------|----------|----------|-------------|--------------------------|
| 3/4" EP Branch Multi-port Tee, 3 (1/2") outlets | Q2237550 | 4.43     | 0.955    | 0.625    | 1.25     | 0.48     | 0.719    | 1.639    | 1.22     | ProPEX 3/4" | 0.1                      |
| 3/4" EP Branch Multi-port Tee, 4 (1/2") outlets | Q2247550 | 5.73     | 0.955    | 0.625    | 1.25     | 0.48     | 0.719    | 1.639    | 1.22     | ProPEX 3/4" | 0.13                     |
| 1" EP Branch Multi-port Tee, 4 (1/2") outlets   | Q2241050 | 6.691    | 1.191    | 0.775    | 1.25     | 0.6      | 0.719    | 1.879    | 1.48     | ProPEX 1"   | -                        |
| 3/4" EP Branch Multi-port Tee, 6 (1/2") outlets | Q2267550 | 8.902    | 0.955    | 0.625    | 1.25     | 0.457    | 0.719    | 1.624    | 1.18     | ProPEX 3/4" | 0                        |
| 1" EP Branch Multi-port Tee, 6 (1/2") outlets   | Q2261050 | 9.251    | 1.191    | 0.625    | 1.25     | 0.57     | 0.719    | 2.009    | 1.441    | ProPEX 1"   | 0                        |

| Part name                 | Part no. | Codes                                      | Standards   | Listings  |
|---------------------------|----------|--|---|---|
| EP branch multi-port tees | All      | UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | ASTM E814 ULC S115 ASTM F877 ASTM F1960 CSA B137.5 ULC S102.2 ASTM E119 UL 263 NSF-61 ULC S101 NSF-14 | IAPMO-ES HUD MR 1269 ICC-ES-PMG cNSFus-pw UL U.P.Code cQAlus P321 |

| Installation   | Related applications   |
|--|------------------------|
| For a mounting bracket, use any product designed to mount 1" copper pipe for the 3/4" multi-port tee or 1 1/4" copper pipe for the 1" multi-port tee. For more information, refer to the Uponor Piping Systems Installation Guide. | PEX-a Plumbing Systems |

| Footnotes | Contact information  |
|-----------|--|
| -         | Uponor Inc.<br>5925 148th Street West<br>Apple Valley, MN 55124<br>T 800.321.4739<br>F 952.891.2008<br><br>Uponor Ltd.<br>6510 Kennedy Road<br>Mississauga, ON L5T 2X4<br>T 888.594.7726<br>F 800.638.9517 |