

Uponor PP-RCT 45 elbows fabricated (butt fusion)

Project Information


Job name :	Location :
Engineer :	Date submitted:
Contractor :	Submitted by:
Manufacturer's representative :	Approved by :

Technical data

Material PP-RCT

Product information and application use

Use Uponor PP-RCT 45 fabricated elbows with Uponor PP-RCT mechanical pipe to convey water for hydronic heating and cooling or industrial applications.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	Weight per UOM [lbs/UOM]	Equivalent length through [ft]	End Type 1	End Type 2	Operating Temperature 1 [°F]
Uponor PP-RCT 45 Elbow, Mechanical, 6" x 6", SDR 11	PR1147645600	6.3	9.95	19.957	12.721	0.58	-	-	Butt 6"	Butt 6"	-
Uponor PP-RCT 45 Elbow, Mechanical, 10" x 10", SDR 17.6	PR174764510	9.85	15.1	30.207	19.477	0.56	17.59	10.9	Butt 10"	Butt 10"	73 °F (23 °C) at 130 psi (23 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 12" x 12", SDR 17.6	PR174764512	12.4	17.6	35.511	23.478	0.705	32.06	13.7	Butt 12"	Butt 12"	73 °F (23 °C) at 130 psi (23 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 6" x 6", SDR 17.6	PR174764560	6.3	9.95	19.754	12.637	0.358	4.72	7	Butt 6"	Butt 6"	73 °F (23 °C) at 130 psi (23 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 8" x 8", SDR 17.6	PR174764580	7.88	17.5	33.607	19.493	0.448	13.06	8.7	Butt 8"	Butt 8"	73 °F (23 °C) at 130 psi (23 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 6" x 6", SDR 9	PR947645600	6.3	9.95	19.754	12.637	0.7	8.43	6	Butt 6"	Butt 6"	73 °F (23 °C) at 265 psi (23 °C)

Part name	Part no.	Operating Temperature 2 [°F]	Operating Temperature 3 [°F]
Uponor PP-RCT 45 Elbow, Mechanical, 6" x 6", SDR 11	PR1147645600	-	-
Uponor PP-RCT 45 Elbow, Mechanical, 10" x 10", SDR 17.6	PR174764510	140 °F (60 °C) at 70 psi (60 °C)	180 °F (82 °C) at 50 psi (82 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 12" x 12", SDR 17.6	PR174764512	140 °F (60 °C) at 70 psi (60 °C)	180 °F (82 °C) at 50 psi (82 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 6" x 6", SDR 17.6	PR174764560	140 °F (60 °C) at 70 psi (60 °C)	180 °F (82 °C) at 50 psi (82 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 8" x 8", SDR 17.6	PR174764580	140 °F (60 °C) at 70 psi (60 °C)	180 °F (82 °C) at 50 psi (82 °C)
Uponor PP-RCT 45 Elbow, Mechanical, 6" x 6", SDR 9	PR947645600	140 °F (60 °C) at 150 psi (60 °C)	180 °F (82 °C) at 100 psi (82 °C)

Installation

Use approved butt-fusion connection methods. Refer to the Uponor PP-RCT manual for complete details.

Related applications

Hydronic heating and cooling systems
Industrial

Codes

CMC|IMC|UMC

Standards

ASTM E84|NSF-14|ASTM F2389|CSA B137.11

Listings

ICC-ES-PMG 1106|IAPMO-R&T 8358|QAI P321-5|IAPMO K-12775

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.636.9517
