

Uponor PP-RCT couplings

Project information


Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Material	PP-RCT
Temp/pressure ratings	73 °F (23 °C) at 340 psi (23.44 bar)
	140 °F (60 °C) at 190 psi (13.1 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)

Product information and application use

Use Uponor PP-RCT couplings with Uponor PP-RCT mechanical pipe to convey water for hydronic heating and cooling or industrial applications.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	Equivalent length through [ft]	End Type 1	End Type 2	Weight per UOM [lbs/UOM]
Uponor PP-RCT Coupling, 1" x 1	PR4771010	0.728	0.118	0.728	1.772	1.575	0.886	0.9	Socket 1"	Socket 1"	0.07
Uponor PP-RCT Coupling, 1 1/4" x 1 1/4	PR4771313	0.846	0.118	0.846	2.244	1.811	1.122	1.1	Socket 1-1/4"	Socket 1-1/4"	0.13
Uponor PP-RCT Coupling, 1 1/2" x 1 1/2	PR4771515	0.945	0.177	0.945	2.736	2.067	1.368	1.4	Socket 1-1/2"	Socket 1-1/2"	0.2
Uponor PP-RCT Coupling, 2" x 2	PR4772020	1.102	0.315	1.102	3.425	2.52	1.713	1.7	Socket 2"	Socket 2"	0.38
Uponor PP-RCT Coupling, 3" x 3	PR4773030	1.319	0.315	1.319	4.764	2.953	2.382	2.5	Socket 3"	Socket 3"	0.86
Uponor PP-RCT Coupling, 4" x 4	PR4774040	1.575	0.236	1.575	6.543	3.386	3.272	4.2	Socket 4"	Socket 4"	1.83
Uponor PP-RCT Coupling, 1/2" x 1/2	PR4775050	0.61	0.197	0.61	1.102	1.417	0.551	0.5	Socket 1/2"	Socket 1/2"	0.03
Uponor PP-RCT Coupling, 3/4" x 3/4	PR4777575	0.689	0.177	0.689	1.339	1.555	0.669	0.7	Socket 3/4"	Socket 3/4"	0.04
Uponor PP-RCT Coupling, 2 1/2" x 2 1/2	PR4772525	1.22	0.177	1.22	3.937	2.618	1.969	2.1	Socket 2-1/2"	Socket 2-1/2"	0.45

Part name	Part no.	Codes	Standards	Listings
Uponor PP-RCT couplings	All	CMC IMC UMC	ASTM E84 ASTM F2389 CSA B137.11	ICC-ES-PMG 1106 IAPMO-R&T 8358 QAI P321-5 IAPMO K-12775
In addition, the following parts have additional codes, standards, or listings:				
Uponor PP-RCT Coupling, 1" x 1	PR4771010		NSF/ANSI 14	
Uponor PP-RCT Coupling, 1 1/4" x 1 1/4	PR4771313		NSF/ANSI 14	
Uponor PP-RCT Coupling, 1 1/2" x 1 1/2	PR4771515		NSF/ANSI 14	
Uponor PP-RCT Coupling, 2" x 2	PR4772020		NSF/ANSI 14	
Uponor PP-RCT Coupling, 3" x 3	PR4773030		NSF/ANSI 14	
Uponor PP-RCT Coupling, 4" x 4	PR4774040		NSF/ANSI 14	
Uponor PP-RCT Coupling, 1/2" x 1/2	PR4775050		NSF-14	
Uponor PP-RCT Coupling, 3/4" x 3/4	PR4777575		NSF-14	
Uponor PP-RCT Coupling, 2 1/2" x 2 1/2	PR4772525		NSF/ANSI 14	

Installation		Related applications	
Use approved socket-fusion connection methods. Refer to the Uponor PP-RCT manual for complete details.		Hydronic heating and cooling systems Industrial	
Footnotes		Contact information	
-		Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517