

Uponor PP-RCT couplings

Project Information


| | |
|---------------------------------|-----------------|
| Job name : | Location : |
| Engineer : | Date submitted: |
| Contractor : | Submitted by: |
| Manufacturer's representative : | Approved by : |

Technical data

| | |
|-----------------------|---|
| Material | PP-RCT |
| Temp/pressure ratings | 73 °F (23 °C) at 340 psi (23.44 bar) 140 °F (60 °C) at 190 psi (13.1 bar) 180 °F (82 °C) at 100 psi (6.9 bar) |

Product Information and application use

Use Uponor PP-RCT couplings with Uponor PP-RCT mechanical pipe to convey water for hydronic heating and cooling or industrial applications.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | Weight per UOM [lbs/UOM] | Equivalent length through [ft] | End Type 1 | End Type 2 |
|--|-----------|----------|----------|----------|----------|----------|----------|--------------------------|--------------------------------|---------------|---------------|
| Uponor PP-RCT Coupling, 1" x 1 | PR4771010 | 0.728 | 0.118 | 0.728 | 1.772 | 1.575 | 0.886 | 0.07 | 0.9 | Socket 1" | Socket 1" |
| Uponor PP-RCT Coupling, 1 1/4" x 1 1/4 | PR4771313 | 0.846 | 0.118 | 0.846 | 2.244 | 1.811 | 1.122 | 0.13 | 1.1 | Socket 1-1/4" | Socket 1-1/4" |
| Uponor PP-RCT Coupling, 1 1/2" x 1 1/2 | PR4771515 | 0.945 | 0.177 | 0.945 | 2.736 | 2.067 | 1.368 | 0.2 | 1.4 | Socket 1-1/2" | Socket 1-1/2" |
| Uponor PP-RCT Coupling, 2" x 2 | PR4772020 | 1.102 | 0.315 | 1.102 | 3.425 | 2.52 | 1.713 | 0.38 | 1.7 | Socket 2" | Socket 2" |
| Uponor PP-RCT Coupling, 2 1/2" x 2 1/2 | PR4772525 | 1.22 | 0.177 | 1.22 | 3.937 | 2.618 | 1.969 | 0.45 | 2.1 | Socket 2-1/2" | Socket 2-1/2" |
| Uponor PP-RCT Coupling, 3" x 3 | PR4773030 | 1.319 | 0.315 | 1.319 | 4.764 | 2.953 | 2.382 | 0.86 | 2.5 | Socket 3" | Socket 3" |
| Uponor PP-RCT Coupling, 4" x 4 | PR4774040 | 1.575 | 0.236 | 1.575 | 6.543 | 3.386 | 3.272 | 1.83 | 4.2 | Socket 4" | Socket 4" |
| Uponor PP-RCT Coupling, 1/2" x 1/2 | PR4775050 | 0.61 | 0.197 | 0.61 | 1.102 | 1.417 | 0.551 | 0.03 | 0.5 | Socket 1/2" | Socket 1/2" |
| Uponor PP-RCT Coupling, 3/4" x 3/4 | PR4777575 | 0.689 | 0.177 | 0.689 | 1.339 | 1.555 | 0.669 | 0.04 | 0.7 | Socket 3/4" | Socket 3/4" |

Installation

Use approved socket-fusion connection methods. Refer to the Uponor PP-RCT manual for complete details.

Related applications

Hydronic heating and cooling systems
Industrial

Codes

CMC|IMC|UMC

Standards

ASTM E84|NSF-14|ASTM F2389|CSA B137.11

Listings

ICC-ES-PMG 1106|IAPMO-R&T 8358|QAI P321-5|IAPMO K-12775

Trademark information

ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.636.9517