υροποι


ProPEX baseboard elbows

| Project Information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |
| | |

| recimical data | |
|-------------------------|-------------------------------------|
| Material | Brass |
| End type 2 | Sweat 3/4" |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) |
| | 180 °F (82 °C) at 100 psi (6.9 bar) |
| | 200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes |
| | |

Product information and application use

The Uponor ProPEX® Baseboard elbow Copper Adapter can be used in any heating system applying the use of fin-tube baseboard or unit-type heaters. One end of the tee adapter features a ProPEX fitting for an easy transition from copper pipe to Wirsbo hePEXTM tubing or Uponor AquaPEX® tubing.



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | End Type 1 | Weight per UOM [lbs/UOM] |
|-------------------------------------------------------------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|------------------|--------------------------------|
| ProPEX Baseboard Elbow, 1/2" PEX x 3/4" Copper Adapter | Q4385075 | 1.796 | 0.307 | 1.489 | 0.611 | 0.709 | 1.81 | 0.987 | 0.75 | ProPEX 1/2" | 0.17 |
| ProPEX Baseboard Elbow, 5/8" PEX x 3/4" Copper Adapter | Q4386375 | 1.861 | 0.372 | 1.489 | 0.614 | 0.866 | 1.974 | 1.04 | 0.75 | ProPEX 5/8" | 0.17 |
| ProPEX Baseboard Elbow, 3/4" PEX x 3/4" Copper Adapter | Q4387575 | 1.924 | 0.435 | 1.489 | 0.615 | 0.945 | 2.054 | 1.2 | 0.75 | ProPEX 3/4" | 0.36 |
| ProPEX Baseboard Elbow, 1/2" PEX x 3/4" Copper Fitting Adapter | Q4375075 | 1.796 | 0.307 | 1.489 | 0.611 | 0.709 | 1.81 | 0.987 | 0.81 | ProPEX 1/2" | 0.38 |
| ProPEX Baseboard Elbow, 5/8" PEX x 3/4" Copper Fitting Adapter | Q4376375 | 1.861 | 0.372 | 1.489 | 0.614 | 0.866 | 2.03 | 1.04 | 0.81 | ProPEX 5/8" | 0.38 |
| ProPEX Baseboard Elbow, 3/4" PEX x 3/4" Copper Fitting Adapter | Q4377575 | 1.924 | 0.435 | 1.489 | 0.615 | 0.945 | 2.13 | 1.2 | 0.81 | ProPEX 3/4" | 0.2 |

| Part name | Part no. | Codes | Standards | Listings |
|-------------------------|----------|-------|--------------------------------------------|--------------------------------|
| ProPEX baseboard elbows | All | IMC | ASTM F1960 CSA B137.5 NSF- 14 ASTM F877 | IAPMO-ES ICC-ES-PMG cNSFus-rfh |

| Installation | Related applications | |
|-----------------------------------------------------------------------------------------------------|-------------------------------------|--|
| | Radiant Heating and Cooling Systems | |
| Use the appropriate ProPEX Ring for tubing (sold separately). Do not solder within 18 inches of the | Permafrost Protection Systems | |

ProPEX connection. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.

Permafrost Protection System

Turf Conditioning Systems

AquaSAFE™ Fire Safety Systems

| Footnotes | Contact information | | | |
|-----------|------------------------|-------------------------|--|--|
| | Uponor Inc. | Uponor Ltd. | | |
| | 5925 148th Street West | 6510 Kennedy Road | | |
| | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | |
| | T 800.321.4739 | T 888.594.7726 | | |
| | F 952.891.2008 | F 800.638.9517 | | |