

Sello de pared de compresión

Project Information


Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Rubber
Prop 65 label required?	Yes

Product Information and application use

Ecoflex® compression wall seals can be used with wall sleeves, or can be used alone where a field core drill is preferred. It creates a watertight seal between the core drill surface and the outer jacket of Ecoflex piping



Part name	Part no.	Subcomponent Material
Compression Wall Seal for 2.7" Jacket	1007358	Hardware: Galvanized steel Rubber gasket: (EPDM) rubber
Compression Wall Seal for 5.5" Jacket	1007360	Hardware: Galvanized steel Rubber gasket: (EPDM) rubber
Compression Wall Seal for 6.9" Jacket	1007361	Hardware: Galvanized steel Rubber gasket: (EPDM) rubber
Compression Wall Seal for 7.9" Jacket	1007362	Hardware: Galvanized steel Rubber gasket: (EPDM) rubber

Installation

For new concrete walls, install over the pipe and Ecoflex compression wall seals into the wall sleeve for a watertight seal. For an existing wall with a field core drill, install between core drill surface and outer jacket of the Ecoflex pipe. Refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual for more information.

Related applications

- Pre-Insulated Pipe Systems
- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

Notes

- Core Drill OD - 4.75"
- Core Drill OD - 8"
- Core Drill OD - 10"

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517