

Bobinas de tuberías térmicas simples Ecoflex

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	PEX
Subcomponent Material	Material Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

Uponor's Ecoflex® Thermal Single is a pre-insulated pipe for buried or aboveground commercial and residential hydronic heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX-a) tubing with multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with ProPEX® Fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings.



Part name	Part no.	R value
3/4" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012775	9.3
1" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012710	7.4
1" Thermal Single with 5.5" Jacket, 600-ft. coil	5015510	12.3
1 1/4" Thermal Single with 5.5" Jacket, 500-ft. coil	5015513	10.7
1 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016915	10.8
2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016920	8.9
2 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016925	7.2
3" Thermal Single with 7.9" Jacket, 300-ft. coil	5017930	7
4" Thermal Single with 7.9" Jacket, 300-ft. coil	5017940	4.8

Part name	Part no.	Codes	Standards	Listings
Bobinas de tuberías térmicas simples Ecoflex	All	UPC IPC NPC of Canada UMC NSPC IMC	ASTM F1960 NSF/ANSI/CAN 61 NSF/ANSI 14	cNSFus-rfh cNSFus-pw U.P.Code
In addition, the following parts have additional codes, standards, or listings:				
3/4" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012775		CSA B137.5	
1" Thermal Single with 2.7" Jacket, 1,000-ft. coil	5012710		ASTM F877 ASTM F876	
1" Thermal Single with 5.5" Jacket, 600-ft. coil	5015510		ASTM F877 ASTM F876	
1 1/4" Thermal Single with 5.5" Jacket, 500-ft. coil	5015513		ASTM F877 ASTM F876	
1 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016915		ASTM F877 ASTM F876	
2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016920		ASTM F877 ASTM F876	
2 1/2" Thermal Single with 6.9" Jacket, 300-ft. coil	5016925		ASTM F877 CSA B137.5 ASTM F876	
3" Thermal Single with 7.9" Jacket, 300-ft. coil	5017930		ASTM F877 CSA B137.5 ASTM F876	
4" Thermal Single with 7.9" Jacket, 300-ft. coil	5017940		ASTM F877 CSA B137.5 ASTM F876	

Installation	Related applications	
Install Ecoflex Thermal Single pre-insulated pipe in buried or aboveground hydronic heating and cooling applications. Use Uponor ProPEX or WIPEX DZR brass compression fittings. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.	Pre-Insulated Pipe Systems	
	Hydronic Heating and Cooling Systems	
	Radiant Heating and Cooling Systems	
	Permafrost Prevention Systems	
	Turf Conditioning Systems	
Footnotes	Contact information	
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517