

Bobinas de tuberías térmicas dobles Ecoflex

Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product Information and application use

Uponor's Ecoflex® Thermal Twin is a pre-insulated pipe system for buried or aboveground commercial and residential hydronic heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX-a) tubing, protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with Uponor ProPEX® fittings or WIPEX™ dezincification-resistant (DZR) brass compression fittings.



Part name	Part no.	Subcomponent Material	R value
1" Thermal Twin with 6.9" Jacket, 600-ft. coil	5026910	Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected	11.3
1 1/4" Thermal Twin Jr. with 5.5" Jacket, 600-ft. coil	5025513	Jacket: Corrugated seamless high-density polyethylene (HDPE); ?UV-protected	7.4
1 1/4" Thermal Twin with 6.9" Jacket, 500-ft. coil	5026913	Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected	9.5
1 1/2" Thermal Twin with 6.9" Jacket, 300-ft. coil	5026915	Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected	7.7
2" Thermal Twin with 7.9" Jacket, 300-ft. coil	5027920	Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected	6.5
2 1/2" Thermal Twin with 7.9" Jacket, 300-ft. coil	5027925	Jacket: Corrugated seamless high-density polyethylene (HDPE); UV-protected	4.5

Part name	Part no.	Codes	Standards	Listings
Bobinas de tuberías térmicas dobles Ecoflex	All	UPC IPC NPC of Canada UMC NSPC IMC	ASTM F877 ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14	cNSFus-rfh cNSFus-pw U.P.Code

Installation	Related applications
Install Ecoflex Thermal Twin pre-insulated pipe in buried or aboveground hydronic heating and cooling applications. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.	Pre-Insulated Pipe Systems Hydronic Heating and Cooling Systems Radiant Heating and Cooling Systems Permafrost Prevention Systems Turf Conditioning Systems AquaSAFE™ Fire Safety Systems

FootnotesContact information

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---