

# Bobinas de tuberías de agua potable simples Ecoflex PEX

## Project Information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

## Technical data

Material	PEX
Subcomponent Material	Jacket: Corrugated, seamless high-density polyethylene (HDPE); UV-protected
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)



## Product information and application use

Ecoflex® Potable PEX Single features Uponor AquaPEX® service pipe protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use Ecoflex Potable PEX Single for hot and cold potable-water applications.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

Part name	Part no.	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	R value	Weight per UOM [lbs/UOM]
3/4" Potable PEX with 2.7" Jacket, 1,000-ft. coil	5212775	2.7	12	2.7	0.671	0.875	9.3	0.35
1" Potable PEX with 2.7" Jacket, 1,000-ft. coil	5212710	2.7	12	2.7	0.862	1.125	7.4	0.38
1" Potable PEX with 5.5" Jacket, 600-ft. coil	5215510	5.5	12	5.5	0.862	1.125	12.3	0.75
1 1/4" Potable PEX with 5.5" Jacket, 500-ft. coil	5215513	5.5	12	5.5	1.054	1.375	10.7	0.85
1 1/2" Potable PEX with 6.9" Jacket, 300-ft. coil	5216915	6.9	12	6.9	1.244	1.625	10.8	1.4
2" Potable PEX with 6.9" Jacket, 300-ft. coil	5216920	6.9	12	6.9	1.629	2.125	8.9	1.8
3" Potable PEX with 7.9" Jacket, 300-ft. coil	5217930	7.9	12	7.9	2.398	3.125	7	2.8

Part name	Part no.	Codes	Standards	Listings
Bobinas de tuberías de agua potable simples Ecoflex PEX	All	UPC IPC NPC of Canada NSPC	ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 ASTM F2023 ASTM F877	U.P.Code

## Installation

Install Ecoflex Potable PEX Single in hot or cold potable-water applications. Join pipes using Uponor ProPEX®. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For additional information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

## Related applications

- Pre-Insulated Pipe Systems
- Permafrost Prevention Systems
- Plumbing Systems

## Footnotes

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517