

Bobinas de tuberías de agua potable simples Ecoflex PEX

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-----------------------|--|
| Material | PEX |
| Subcomponent Material | Jacket: Corrugated, seamless high-density polyethylene (HDPE); UV-protected |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) |

Product information and application use

Ecoflex® Potable PEX Single features Uponor AquaPEX® service pipe protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use Ecoflex Potable PEX Single for hot and cold potable-water applications.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name | Part no. | R value |
|---|----------|---------|
| 3/4" Potable PEX with 2.7" Jacket, 1,000-ft. coil | 5212775 | 9.3 |
| 1" Potable PEX with 2.7" Jacket, 1,000-ft. coil | 5212710 | 7.4 |
| 1" Potable PEX with 5.5" Jacket, 600-ft. coil | 5215510 | 12.3 |
| 1 1/4" Potable PEX with 5.5" Jacket, 500-ft. coil | 5215513 | 10.7 |
| 1 1/2" Potable PEX with 6.9" Jacket, 300-ft. coil | 5216915 | 10.8 |
| 2" Potable PEX with 6.9" Jacket, 300-ft. coil | 5216920 | 8.9 |
| 3" Potable PEX with 7.9" Jacket, 300-ft. coil | 5217930 | 7 |

| Part name | Part no. | Codes | Standards | Listings |
|---|----------|----------------------------|--|----------|
| Bobinas de tuberías de agua potable simples Ecoflex PEX | All | UPC IPC NPC of Canada NSPC | ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 ASTM F2023 ASTM F877 | U.P.Code |

Installation

Install Ecoflex Potable PEX Single in hot or cold potable-water applications. Join pipes using Uponor ProPEX®. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For additional information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

Pre-Insulated Pipe Systems
Permafrost Prevention Systems
Plumbing Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517