Bobinas de tuberías de agua potable simples Ecoflex PEX

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
	· · · · · · · · · · · · · · · · · · ·
Manufacturer's representative:	Approved by:

Technical data	
Material	PEX
Subcomponent Material	Jacket:
	Corrugated, seamless high-density polyethylene
	(HDPE); UV-protected
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

Ecoflex® Potable PEX Single features Uponor AquaPEX® service pipe protected by multilayer PEXfoam insulation and covered by a corrugated, waterproof HDPE jacket. Use Ecoflex Potable PEX Single for hot and cold potable-water applications.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding applicationspecific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



uponor

Part name	Part no.	R value
3/4" Potable PEX with 2.7" Jacket, 1,000-ft. coil	5212775	9.3
1" Potable PEX with 2.7" Jacket, 1,000-ft. coil	5212710	7.4
1" Potable PEX with 5.5" Jacket, 600-ft. coil	5215510	12.3
1 1/4" Potable PEX with 5.5" Jacket, 500-ft. coil	5215513	10.7
1 1/2" Potable PEX with 6.9" Jacket, 300-ft. coil	5216915	10.8
2" Potable PEX with 6.9" Jacket, 300-ft. coil	5216920	8.9
3" Potable PEX with 7.9" Jacket, 300-ft. coil	5217930	7

Part name	Part no.	Codes	Standards	Listings
Bobinas de tuberías de agua potable simples Ecoflex PEX	All	UPC IPC NPC of Canada NSPC	ASTM F1960 CSA B137.5 NSF/ANSI/CAN 61 ASTM F876 NSF/ANSI 14 ASTM F2023 ASTM F877	U.P.Code

Installation	Related applications
Install Ecoflex Potable PEX Single in hot or cold potable-water applications. Join pipes using Uponor ProPEX®. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For additional information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.	Pre-Insulated Pipe Systems Permafrost Prevention Systems Plumbing Systems

Footnotes	Contact information	
	Uponor Inc.	Uponor Ltd.
	5925 148th Street West	6510 Kennedy Road
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4
	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.638.9517