

Tapas de caucho de EPDM para tuberías simples

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Subcomponent Material	Rubber End Cap: EPDM (ethylene propylene diene monomer) rubber; Clamp Device: Stainless steel; O-ring: EPDM rubber
-----------------------	--

Product information and application use

Use the EPDM Rubber End Cap to seal the exposed insulation between the jacket and service pipe when cutting pipe to make a connection. Designed to support system integrity, Ecoflex® End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination.



Part name	Part no.	Weight per UOM [lbs/UOM]
End Cap, 3/4" and 1" Pipe with 2.7" Jacket	5852710	0.4
End Cap, 1" and 1 1/4" PEX Pipe with 5.5" Jacket	5855513	1.0009
End Cap, 1 1/4", 1 1/2" and 2" HDPE Pipe with 5.5" Jacket	5855520	1.0009
End Cap, 1 1/2", 2", 2 1/2" PEX and 3" HDPE Pipe with 6.9" Jacket	5856930	1.0009
End Cap 3, 3 1/2, 4" PEX and 4" HDPE pipe, 7.9" Jacket	5857940	1.9

Installation

The End Cap includes an O-ring and clamp device for a water-tight installation. Slip the End Cap on the jacket pipe and ensure that the O-ring stays in place. Refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual for more information.

Related applications

- Pre-Insulated Pipe Systems
- Radiant Heating and Cooling Systems
- Permafrost Prevention Systems
- Turf Conditioning Systems

Notes

- Compatible Pipes 5012775; 5012710; 5212775; 5212710
- Compatible Pipes 5015510; 5015513; 5215510; 5215513
- Compatible Pipes 5115513; 5115515; 5115520
- Compatible Pipes: 5016915; 5016920; 5016925; 5116930; 5216915; 5216920
- Compatible Pipes: 5017930; 5017935; 5017940; 5117940; 5217930

Footnotes

-

Contact information

Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---