

Accesorios para tuberías de agua potable Ecoflex PEX Plus

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Body: polyamide; conductors: nickel-coated brass
Ambient temperature min. [F]	-40 °f
Ambient temperature max. [F]	122 °f

Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



Part name	Part no.	Codes	Standards	Listings
Accesorios para tuberías de agua potable Ecoflex PEX Plus	All	-	-	IECEX SIR 11.0136U

Installation

Simply cut back one wire 1/4" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

- Pre-Insulated Pipe Systems
- Permafrost Prevention Systems
- PEX-a Plumbing Systems

Notes

Power cable:
3c x 2.5mm² (supplied by others)
Power cable entry: Gland provided as standard; insert appropriate supplied bush into the gland

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517