# Accesorios para tuberías de agua potable Ecoflex PEX Plus

## Project information

| | |
|---|---|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

## Technical data

Subcomponent Material
Ambient temperature min. [F] -40 °f
Ambient temperature max. [F] 482 °f

## Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



| | Part name | Part no. | Weight per UOM [lbs/UOM] |
|---|---|---|---|
| | Heat-trace Power Terminal Block | 5992000 | 0.3 |
| ✔ | Heat-trace End Seal | 5993000 | 0.05 |
| | Heat-trace Tee Splice | 5994000 | 0.3 |

| Part name | Part no. | Codes | Standards | Listings |
|---|---|---|---|---|
| Accesorios para tuberías de agua potable Ecoflex PEX Plus | All | - | - | IECEx SIR 11.0136U |

## Installation

Simply cut back one wire ¼" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

## Related applications

Pre-Insulated Pipe Systems

Permafrost Prevention Systems

PEX-a Plumbing Systems

## Notes

Voltage Range 220 to 277

Voltage Range 220 to 277.

## Footnotes

-

## Contact information


Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517


© 2026 Uponor North America. All Rights Reserved