

Accesorios para tuberías de agua potable Ecoflex PEX Plus

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Subcomponent Material	
Ambient temperature min. [F]	-40 °f
Ambient temperature max. [F]	482 °f

Product information and application use

Uponor heat-trace end seal is part of a universal power termination and splicing system for Uponor Ecoflex® potable PEX plus pre-insulated piping systems.



Part name	Part no.	Weight per UOM [lbs/UOM]
Heat-trace Power Terminal Block	5992000	0.3
Heat-trace End Seal	5993000	0.05
Heat-trace Tee Splice	5994000	0.3

Part name	Part no.	Codes	Standards	Listings
Accesorios para tuberías de agua potable Ecoflex PEX Plus	All	-	-	IECEX SIR 11.0136U

Installation

Simply cut back one wire 1/4" (6mm) and push it into the end seal. For additional information, refer to the Uponor Ecoflex Pre-insulated Pipe Systems Design and Installation Manual.

Related applications

Pre-Insulated Pipe Systems
Permafrost Prevention Systems
PEX-a Plumbing Systems

Notes

Voltage Range 220 to 277

Voltage Range 220 to 277.

Footnotes

Contact information

-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
---	---	---