Relés para bombas

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

The Single-zone Pump relay controls the operation of a single circulator or pump from a 24-volt signal. The Three-zone Multi-pump Relay controls the operation of up to three pumps or circulators from dedicated 24-volt signals. The relay includes secondary low-voltage terminals for boiler operation and DHW priority options.



	Part name	Part no.	Operating voltage AC [VAC]	Voltage secondary AC (50VA) [VAC]	Current draw max. [A]	Ambient humidity non-condensing max [%]
✔	Single-zone Pump Relay	A3010100	120	24	-	-
	Three-zone Multi-pump Relay	A3080301	120	-	7.2	90

Installation

Connect the thermostat to the "T T" terminals on the switching relay. When the thermostat calls for heat, the boiler is given a signal to start. The appropriate circulator is only energized when the boiler is above the set low limit. Refer to the Uponor Three-zone Multi-pump Relay Instruction Sheet for additional information.

Related applications

Radiant Heating and Cooling Systems

Notes

Indoor use only!

Maximum Zones:
3 with priority

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2026 Uponor North America. All Rights Reserved