

Termostatos solo para calefacción con pantalla táctil

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

The Uponor Heat-only Thermostat with Touchscreen (A3100101) is a simple, non-programmable thermostat designed to sense room air temperature using operative temperature and/or floor temperature via an optional floor sensor (A9010599).



Part name	Part no.	Current draw max. [A]	Operating voltage AC [VAC]	Output rating at 24VAC [A]
Heat-only Thermostat with Touchscreen	A3100101	0.042	24	1.3
Slab Sensor, 10k	A9010599	-	-	-

Installation	Related applications
Install the thermostat on an interior wall of the desired zone approximately 5 feet above the floor. Do not mount the thermostat on a location that may be affected by localized heat sources or cold drafts. It may be necessary to install a draft barrier behind the thermostat to prevent air from blowing through the wiring hole which can affect the thermostat's built-in sensor. Refer to the Uponor Heat-only Thermostat with Touchscreen Installation and Operation Manual for more information.	Radiant heating systems

Notes
Floor sensor: 10K, J-curve thermistor Ambient conditions: 10% to 90% humidity (non-condensing) Sensor type: 10k J-curve Tolerance: +/- 1% at 77°F (25°C) Wire type: 22 gauge IP68 continuous immersion 3m /10 ft

Footnotes	Contact information
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517