

# Colectores con válvula de cobre y válvulas de bola con rosca R20/R25



## Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

## Technical data

Material	Copper
Manifold size	2 inch
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar) 210 °F (99 °C) at 149 psi (10.3 bar)
Max. fluid flow rate	45 gpm
Prop 65 label required?	Yes



## Product information and application use

The 2" x 4' Copper Valved Manifold with R20/R25 Threaded Ball Valves is designed for radiant heating applications. The manifold has a 2" copper sweat fitting adapter supply connection and 3/4" nominal branches that are 4 inches on center. This 12-outlet manifold comes preassembled with R20 and R25 threaded ball valve connections.

*This product is made to order, please contact [customer service](#) for lead time.*

Part name	Part no.	Cv	End Type 1
2" x 4' Copper Valved Manifold with R20 Threaded Ball Valves, 12 outlets	F2811220	7	ISO 228-G 3/4"
2" x 4' Copper Valved Manifold with R25 Threaded Ball Valves, 12 outlets	F2811225	7.3	ISO 228-G 1"

Part name	Part no.	Codes	Standards	Listings
Colectores con válvula de cobre y válvulas de bola con rosca R20/R25	All	-	CSA B125 CSA B137.5 ASTM F877	cNSFus-rfh

Installation	Related applications
Install using any product designed to mount 2" copper pipe as a mounting bracket. Refer to the Uponor Radiant Floor Heating Installation Handbook for additional information.	Radiant Heating and Cooling Systems Permafrost Protection Systems Turf Conditioning Systems

## Notes

Ball Cv for the R20 outlet:  
7.00  
Ball Cv for the R25 outlet: 7.30

Footnotes	Contact information
-	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517