

Pies de soporte de tuberías PEX

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

| | |
|-------------------------|---------|
| Material | Plastic |
| Subcomponent Material | PVC |
| Prop 65 label required? | Yes |

Product information and application use

Use the PEX Stand-up Bracket in residential slab or commercial multi-floor construction. The brackets are available in either single-tube or five-tube configurations. The bracket supports up to 1" Uponor hePEX™ plus or Uponor AQUAPEX® tubing, or a 1" utility-grade, polyethylene sleeving.



| Part name | Part no. | Weight per UOM [lbs/UOM] |
|---|----------|--------------------------|
| Single-tube PEX Stand-up Bracket for 1/2" PEX | F5801000 | 0.5 |
| Five-tube PEX Stand-up Bracket for 1/2" PEX | F5805000 | 1.1 |

| Installation | Related applications |
|---|---|
| Screw or nail the 3/4" fastening tab to the floor or concrete forms. Secure the brackets to the deck form. Then install the 1/2" PEX tubing in the brackets, either with the 1/2" PEX tubing alone or with the 1/2" PEX tubing sleeved inside corrugated polyethylene carrier tube. Wire the tube at the top of bracket to bracket at the wiring tab. | PEX-a Plumbing Systems Radiant Floor Heating and Cooling Systems |

| Footnotes | Contact information |
|-----------|--|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |