

Accesorios para rociadores contra incendios de bronce sin plomo (LF) ProPEX



Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

End type 1	ProPEX 1/2"
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

Uponor fire sprinkler accessories include the following options sold separately: Fire sprinkler adapter mounting brackets, Fire sprinkler adapter push-on nut (25/package) and Screws. Screws #10 X 1 1/2" pan head, full thread (100/package).



Part name	Part no.	Codes	Standards	Listings
Accesorios para rociadores contra incendios de bronce sin plomo (LF) ProPEX	All	-	-	-

Installation

N/A

Related applications

AquaSAFE™ Fire Safety Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517