## Adaptadores de codos caídos de bronce sin plomo (LF) ProPEX



| Project information            |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Fecha de envío: |
| Contractor:                    | Presentada por: |
| Manufacturer's representative: | Approved by:    |

## Technical data

Material LF Brass

200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

## Product information and application use

Uponor offers the ProPEX® Lead-free Drop Ear Brass Elbow for use in hot and cold domestic potable water systems. One end of the adapter connects to female iron pipe (FIP) and the other end includes an Uponor ProPEX fitting for connections to Uponor AquaPEX® tubing.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



| Part name   | Part no.  | End Type 1  | End Type 2 |
|---|-----------|-------------|------------|
| ProPEX LF Brass Drop Ear Elbow, 1/2" PEX x 3/8" FIP | LF4235038 | ProPEX 1/2" | FNPT 3/8"  |
| ProPEX LF Brass Drop Ear Elbow, 1/2" PEX x 1/2" FIP | LF4235050 | ProPEX 1/2" | FNPT 1/2"  |
| ProPEX LF Brass Drop Ear Elbow, 3/4" PEX x 3/4" FIP | LF4237575 | ProPEX 3/4" | FNPT 3/4"  |
| ProPEX LF Brass Drop Ear Elbow, 1" PEX x 1" FIP     | LF4231010 | ProPEX 1"   | FNPT 1"    |

| Part name                      | Part no. | Codes                  | Standards                      | Listings                        |
|--------------------------------|----------|------------------------|--------------------------------|---------------------------------|
| Adaptadores de codos caídos de | All      | UPC IBC IRC IPC NPC of | NSF-372 ASTM F877 ASTM         | ICC-ES-PMG cNSFus-pw-G U.P.Code |
| bronce sin plomo (LF) ProPEX   | All      | Canada UMC NSPC IMC    | F1960 CSA B137.5 NSF-61 NSF-14 | ICC-E3-FMG CN3Fus-pw-G O.F.Code |

## Installation Related applications

A ProPEX Ring is required for making ProPEX connections. Use the appropriate ProPEX Ring for tubing. For more information, refer to the Uponor Professional Plumbing Installation Guide.

PEX-a Plumbing Systems

| Footnotes | Contact information    |                         |  |
|-----------|------------------------|-------------------------|--|
|           | Uponor Inc.            | Uponor Ltd.             |  |
|           | 5925 148th Street West | 6510 Kennedy Road       |  |
| •         | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 |  |
|           | T 800.321.4739         | T 888.594.7726          |  |
|           | F 952.891.2008         | F 800.638.9517          |  |