

Rociadores ocultos

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required?	Yes
-------------------------	-----

Product information and application use

Concealed sprinklers thread onto Uponor's fire sprinkler adapter fittings. All sprinklers come complete with a plastic protective cap and cup. Sprinklers are NSF- and UL-approved for combined plumbing and fire sprinkler systems. Sprinklers designated LF are also NSF Annex G compliant.



Part name	Part no.	A [inch]	B [inch]	Material group	End Type 1	End Type 2	End Type 3	Weight per UOM [lbs/UOM]
LF RC-RES (162F) Flat Concealed Sprinkler	LF74970FC	-	-	-	-	-	-	0.36
LF RC-RES (205F) Flat Concealed Sprinkler with White Cover Plate	LF74971FW	0	0	LF Brass	ProPEX	ProPEX	FNPT	0.39

Installation

Related applications

Concealed cover plates for LF74970FC sold separately. Concealed cover plates are included with LF74971FW. Do not store sprinkler assemblies where the ambient temperature will exceed 100°F. Special sprinkler wrenches are required to assemble sprinkler and adapter.

AquaSAFE™ Fire Safety Systems

Footnotes

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517