Tapones de EP ProPEX

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Engineered Polymer
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)



Product information and application use

ProPEX® engineered polymer (EP) plugs terminate Uponor crosslinked polyethylene (PEX-a) tubing ends and are available for use in hot and cold domestic potable water systems, residential fire sprinkler systems and hydronic heating and cooling systems.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.

	Part name	Part no.	End Type 1
	ProPEX EP Plug for 1/2" PEX	Q4350500	ProPEX 1/2"
	ProPEX EP Plug for 3/4" PEX	Q4350750	ProPEX 3/4"
	ProPEX EP Plug for 1" PEX	Q4351000	ProPEX 1"
	ProPEX EP Plug for 1 1/4" PEX	Q4351250	ProPEX 1-1/4"
	ProPEX EP Plug for 1 1/2" PEX	Q4351500	ProPEX 1-1/2"
✔	ProPEX EP Plug for 2" PEX	Q4352000	ProPEX 2"

Part name	Part no.	Codes	Standards	Listings
Tapones de EP ProPEX	All	UPC|IBC|IRC|IPC|NPC of Canada|UMC|NSPC|IMC	ASTM E814/ULC S115|ASTM F877|ASTM F1960|CSA B137.5|ULC S102.2|ASTM E119/UL 263|ULC S101	IAPMO-ES|HUD MR 1269|ICC-ES-PMG|UL|U.P.Code|cQAIus P321
In addition, the following parts have additional codes, standards, or listings:				
ProPEX EP Plug for 1/2" PEX	Q4350500		NSF/ANSI/CAN 61|NSF/ANSI 14	cNSFus-pw
ProPEX EP Plug for 3/4" PEX	Q4350750		UL 1821|NSF-61|NSF-14	cNSFus-pw-fs
ProPEX EP Plug for 1" PEX	Q4351000		UL 1821|NSF-61|NSF-14	cNSFus-pw-fs
ProPEX EP Plug for 1 1/4" PEX	Q4351250		UL 1821|NSF-61|NSF-14	cNSFus-pw-fs
ProPEX EP Plug for 1 1/2" PEX	Q4351500		NSF-61|NSF-14	cNSFus-pw
ProPEX EP Plug for 2" PEX	Q4352000		NSF/ANSI/CAN 61|NSF/ANSI 14	cNSFus-pw

Installation

Note: ProPEX tool is required. ProPEX rings sold separately.

Related applications

PEX-a Plumbing Systems

Hydronic Radiant Heating and Cooling Systems

Turf Conditioning Systems

Permafrost Prevention Systems

AquaSAFE™ Fire Safety Systems

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved