

## Adaptadores soldados de bronce ProPEX

Project information	
Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

## Technical data

Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar)


180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

## Product information and application use

ProPEX® brass sweat adapters transition Uponor PEX pipe to copper pipe for use in hydronic heating and cooling systems. One end of the adapter is manufactured with the Uponor ProPEX fitting for connection to Wirsbo hePEX™ pipe and the other end is manufactured to adapt copper sweat connections. These adapters are not safe for direct burial in soil. Note: Not for potable use.

Note: Temperature and pressure ratings stated are hydrostatic ratings. For domestic hot-water (DHW) and DHW recirculation installations, operating conditions should not exceed 140°F (60°C) at 80 psi (5.5 bar) in accordance with ASTM F2023. For additional information regarding application-specific temperature and pressure ratings, refer to the Uponor PEX Piping Systems Design and Installation Manual.



Part no.	Cv	Material group	End Type 1	End Type 2
LF4513850	5.7	LF Brass	ProPEX 3/8"	Sweat 1/2"
Q5515050	5.7	Brass	ProPEX 1/2"	Sweat 1/2"
LF4515075	5.1	LF Brass	ProPEX 1/2"	Sweat 3/4"
Q4516350	-	Brass	ProPEX 5/8"	Sweat 1/2"
Q4516375	-	Brass	ProPEX 5/8"	Sweat 3/4"
Q5517550	8.8	Brass	ProPEX 3/4"	Sweat 1/2"
Q5517575	13.4	Brass	ProPEX 3/4"	Sweat 3/4"
Q5517510	10.9	Brass	ProPEX 3/4"	Sweat 1"
Q5511010	22.1	Brass	ProPEX 1"	Sweat 1"
Q5511313	34	Brass	ProPEX 1-1/4"	Sweat 1-1/4"
Q5512020	83.6	Brass	ProPEX 2"	Sweat 2"
LF4513030	189.1	LF Brass	ProPEX 3"	Sweat 3"
Q5511515	45.5	Brass	ProPEX 1-1/2"	Sweat 1-1/2"
	LF4513850  Q5515050  LF4515075  Q4516350  Q4516375  Q5517550  Q5517575  Q5517510  Q5511010  Q5511313  Q5512020  LF4513030	LF4513850 5.7  Q5515050 5.7  LF4515075 5.1  Q4516350 -  Q4516375 -  Q5517550 8.8  Q5517575 13.4  Q5517570 10.9  Q5511010 22.1  Q5511313 34  Q5512020 83.6  LF4513030 189.1	LF4513850         5.7         LF Brass           Q5515050         5.7         Brass           LF4515075         5.1         LF Brass           Q4516350         -         Brass           Q4516375         -         Brass           Q5517550         8.8         Brass           Q5517575         13.4         Brass           Q5517510         10.9         Brass           Q5511010         22.1         Brass           Q5511313         34         Brass           Q5512020         83.6         Brass           LF4513030         189.1         LF Brass	LF4513850         5.7         LF Brass         ProPEX 3/8"           Q5515050         5.7         Brass         ProPEX 1/2"           LF4515075         5.1         LF Brass         ProPEX 1/2"           Q4516350         -         Brass         ProPEX 5/8"           Q4516375         -         Brass         ProPEX 5/8"           Q5517550         8.8         Brass         ProPEX 3/4"           Q5517575         13.4         Brass         ProPEX 3/4"           Q5517510         10.9         Brass         ProPEX 3/4"           Q5511010         22.1         Brass         ProPEX 1"           Q5511313         34         Brass         ProPEX 1-1/4"           Q5512020         83.6         Brass         ProPEX 2"           LF4513030         189.1         LF Brass         ProPEX 3"

Part name	Part no.	Codes	Standards	Listings			
Adaptadores soldados de bronce ProPEX	All	IBC IRC NPC of Canada UMC IMC	ASTM F877 ASTM F1960 CSA B137.5 NSF-14	IAPMO-ES ICC-ES-PMG			
In addition, the following parts have additional codes, standards, or listings:							
ProPEX LF Brass Sweat Adapter, 3/8" PEX x 1/2" Copper	LF4513850	UPC IPC NSPC	NSF-372 NSF-61	cNSFus-pw-G U.P.Code			
ProPEX Brass Sweat Adapter, 1/2" PEX x 1/2" Copper	Q5515050			cNSFus-rfh			
ProPEX LF Brass Sweat Adapter, 1/2" PEX x 3/4" Copper	LF4515075	UPC IPC NSPC	NSF-372 NSF-61	cNSFus-pw-G U.P.Code			
ProPEX Brass Sweat Adapter, 5/8" PEX x 1/2" Copper	Q4516350			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 5/8" PEX x 3/4" Copper	Q4516375			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 3/4" PEX x 1/2" Copper	Q5517550			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 3/4" PEX x 3/4" Copper	Q5517575			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 3/4" PEX x 1" Copper	Q5517510			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 1" PEX x 1" Copper	Q5511010			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 1 1/4" PEX x 1 1/4" Copper	Q5511313			cNSFus-rfh			
ProPEX Brass Sweat Adapter, 2" PEX x 2" Copper	Q5512020			cNSFus-rfh			
ProPEX LF Brass Sweat Adapter, 3" PEX x 3" Copper	LF4513030	UPC IPC NSPC	NSF-372 NSF-61	cNSFus-pw-G U.P.Code			
ProPEX Brass Sweat Adapter, 1 1/2" PEX x 1 1/2" Copper	Q5511515			cNSFus-rfh			

Installation Related applications

Use the appropriate Uponor ProPEX ring for the pipe (sold separately). Do not solder within 18" of the ProPEX fitting. Refer to the Radiant Floor Heating Installation Handbook, Complete Design Assistance Manual (CDAM), or the Hydronic Piping Design Assistance Manual (HPDAM) for additional information.

Radiant Heating and Cooling Systems
Permafrost Protection Systems
Turf Conditioning Systems
Hydronic Piping Systems

Footnotes	Contact in	Contact information		
	Uponor Inc.	Uponor Ltd.		
	5925 148th Street West	6510 Kennedy Road		
	Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
	T 800.321.4739	T 888.594.7726		
	F 952.891.2008	F 800.638.9517		