

Tapas ocultas planas

Project information

| | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Fecha de envío: |
| Contractor: | Presentada por: |
| Manufacturer's representative: | Approved by: |

Technical data

Prop 65 label required? Yes

Product information and application use

Concealed flat cover plates easily slide onto flat concealed sprinklers for a finished appearance. The flat cover plate completely hides the sprinkler from view. All cover plates detach from the sprinkler assembly when temperatures reach 135°F (57.2°C) to 140°F (60°C).



| Part name | Part no. | Weight per UOM [lbs/UOM] |
|---|----------|--------------------------|
| Concealed Flat Cover Plate for HSW, White, (HSW style only) | Q70640HW | 0.13 |
| Concealed Flat Cover Plate for 162F LF RC-RES Sprinkler, White, 3 1/4 | Q70749WH | 0.1 |

| Installation | Related applications |
|---|-------------------------------|
| Do not store cover plates in areas where the ambient temperature will exceed 100°F (37.7°C). Cover plates must be used with LF RC-RES concealed sprinklers and LF concealed horizontal sidewall sprinklers. | AquaSAFE™ Fire Safety Systems |

| Footnotes | Contact information | |
|-----------|---|---|
| - | Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008 | Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517 |