Soportes de tuberías PEX-a

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



	Part name	Part no.	A [inch]	B [inch]	C [inch]	Material group	Subcomponent Material	Prop 65 label required?	Weight per UOM [lbs/UOM]
	1/2" PEX-a Pipe Support, 9-ft. length	F7040500	108	0.677	0.406	Metal	Commercial-grade (Type B) galvanized steel	-	1.1
	3/4" PEX-a Pipe Support, 9-ft. length	F7040750	108	0.921	0.552	Metal	Commercial-grade (Type B) galvanized steel	No	1.5
	1" PEX-a Pipe Support, 9-ft. length	F7041000	108	1.163	0.698	Metal	Commercial-grade (Type B) galvanized steel	-	1.91
	1 1/4" PEX-a Pipe Support, 9-ft. length	F7041250	108	1.396	0.837	Metal	Commercial-grade (Type B) galvanized steel	-	2.1
	1 1/2" PEX-a Pipe Support, 9-ft. length	F7041500	108	1.623	0.973	Metal	Commercial-grade (Type B) galvanized steel	-	2.5
	2" PEX-a Pipe Support, 9-ft. length	F7042000	108	2.095	1.256	Metal	Commercial-grade (Type B) galvanized steel	-	3.6
	2 1/2" PEX-a Pipe Support, 9-ft. length	F7042500	108	2.562	1.537	Metal	Commercial-grade (Type B) galvanized steel	-	4.6
	PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX	Q7410510	-	-	-	Plastic	-	-	0
	3" PEX-a Pipe Support, 9-ft. length	F7043000	108	3.024	1.81	Metal	Commercial-grade (Type B) galvanized steel	-	6.2
	PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX	Q7411220	-	-	-	Plastic	-	-	0.01
✔	PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX	Q7412540	-	-	-	Plastic	-	-	0.01

Part name	Part no.	Codes	Standards	Listings
Soportes de tuberías PEX-a	All	IMC|UMC	ASTM E84	QAI P321 (up to 3")

Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

Related applications

PEX-a Plumbing Systems

Radiant Heating and Cooling Systems

AquaSAFE™ Fire Safety Systems

© 2026 Uponor North America. All Rights Reserved

Footnotes	Contact information	
	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
-		

© 2026 Uponor North America. All Rights Reserved