Válvulas de bola de bronce ProPEX

Project information	
Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

 Cv
 132.2

 Material
 Brass

 Subcomponent Material
 Seal:

 PTFE
 End type 1

 ProPEX


End type 1 ProPEX 2"
End type 2 ProPEX 2"
Cold working pressure 200.2 psi

Temp/pressure ratings 73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)

Prop 65 label required? Yes

Product information and application use

Uponor ProPEX® Brass Ball Valve is a cost-effective alternative for radiant heating/cooling and hydronic piping applications. Both ends are manufactured with the ProPEX fitting for connections to Uponor PEX pipe. The full-port valves are compatible with propylene glycol mixtures up to 50%. Stem extensions can be installed to accommodate up to 2" of pipe insulation. Note: ProPEX Brass Ball Valves are not approved for potable-water applications.



Part name	Part	A	B	C	D	E	F	G	H	l	J
	no.	[inch]									
ProPEX Brass Ball Valve 2" PEX x 2" PEX	A3202020	2.147	2.834	3.374	5.57	1.467	1.103	9.448	4.831	2.915	7.128

Part name	Part no.	Weight per UOM [lbs/UOM]
ProPEX Brass Ball Valve 2" PEX x 2"		4.18

Part name	Part no.	Codes	Standards	Listings
Válvulas de bola de bronce ProPEX	A3202020	IMC UMC	ASTM F1960 CSA B137.5 NSF/ANSI	cNSFus-rfh

Installation Related applications Hot water distribution Hydronic heating and cooling systems Hydronic Piping Systems Hydronic Radiant Heating and Cooling Systems PEX-a Plumbing Systems Plumbing Systems Pre-Insulated Pipe Systems Radiant Floor Heating and Cooling Systems Radiant Heating and Cooling Systems Pre-Insulated Pipe Systems Radiant Heating and Cooling Systems

	Footnotes	Contact ir	Contact information		
		Uponor Inc.	Uponor Ltd.		
		5925 148th Street West	6510 Kennedy Road		
-		Apple Valley, MN 55124	Mississauga, ON L5T 2X4		
		T 800.321.4739	T 888.594.7726		
		F 952.891.2008	F 800.638.9517		