

Mallas Radiant Rollout

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

The Radiant Rollout™ Mat features 1/2" or 5/8" Wirsbo hePEXTM tubing that has an oxygen-diffusion barrier that meets German DIN 4726/9. The mat can include a 3/4" reverse-return header with 3/4" ProPEX EP fittings that is pressurized to 20 psi to ensure system integrity. The mat can also be designed without a reverse-return header. In this instance, it is not prepressurized and can connect to a wall manifold such as the TruFLOW™ Classic Manifold



Part name	Part no.	Subcomponent Material
1/2" Wirsbo hePEX Radiant Rollout Mat (6" o.c.), 5 loop	M2306060000	UDEL polysulfone (PSU) 20% glass-reinforced for ProPEX engineered polymer (EP) fittings; Acetal polymer for support strip bracing; Nylon zip ties; Brass Schrader valve
1/2" Wirsbo hePEX Radiant Rollout Mat (9" o.c.), 3 loop	M2309054000	UDEL polysulfone (PSU) 20% glass-reinforced for ProPEX engineered polymer (EP) fittings Acetal polymer for support strip bracing; Nylon zip ties; Brass Schrader valve
1/2" Wirsbo hePEX Radiant Rollout Mat (12" o.c.), 3 loop	M2312072000	UDEL polysulfone (PSU) 20% glass-reinforced for ProPEX engineered polymer (EP) fittings Acetal polymer for support strip bracing; Nylon zip ties; Brass Schrader valve
5/8" Wirsbo hePEX Radiant Rollout Mat (6" o.c.), 5 loop	M2406060000	UDEL polysulfone (PSU) 20% glass-reinforced for ProPEX engineered polymer (EP) fittings Acetal polymer for support strip bracing; Nylon zip ties; Brass Schrader valve
5/8" Wirsbo hePEX Radiant Rollout Mat (9" o.c.), 3 loop	M2409054000	UDEL polysulfone (PSU) 20% glass-reinforced for ProPEX engineered polymer (EP) fittings Acetal polymer for support strip bracing; Nylon zip ties; Brass Schrader valve
5/8" Wirsbo hePEX Radiant Rollout Mat (12" o.c.), 3 loop	M2412072000	UDEL polysulfone (PSU) 20% glass-reinforced for ProPEX engineered polymer (EP) fittings Acetal polymer for support strip bracing; Nylon zip ties; Brass Schrader valve

Part name	Part no.	Codes	Standards	Listings
Mallas Radiant Rollout	All	IMC UPC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC	ASTM F1960 ASTM E119/UL 263 ASTM F876 ASTM E84 ASTM F2023 ASTM E814/ULC S115 ASTM F877 CSA B137.5 ULC S102.2 CSA B214 NSF-61 ULC S101 NSF-14	IAPMO-ES ICC-ES-PMG cNSFusrfh CCMC PPI TR-4 CSA UL cQAIus P321 HUD MR 1269
In addition, the following parts have additional codes, standards, or listings:				
1/2" Wirsbo hePEX Radiant Rollout Mat (6" o.c.), 5 loop	M2306060000			
1/2" Wirsbo hePEX Radiant Rollout Mat (9" o.c.), 3 loop	M2309054000			
1/2" Wirsbo hePEX Radiant Rollout Mat (12" o.c.), 3 loop	M2312072000			
5/8" Wirsbo hePEX Radiant Rollout Mat (6" o.c.), 5 loop	M2406060000			
5/8" Wirsbo hePEX Radiant Rollout Mat (9" o.c.), 3 loop	M2409054000			
5/8" Wirsbo hePEX Radiant Rollout Mat (12" o.c.), 3 loop	M2412072000			

Installation		Related applications	
At the jobsite, roll out the mat and, depending on your header/manifold selection, connect to a supply-and-return line using the attached header (optional) or connect each loop to a wall manifold (optional). Contact your local Uponor representative for more information.		Radiant Heating and Cooling Systems	
		Permafrost Protection Systems	
		Turf Conditioning Systems	
Notes			
5' wide; place every 7' length; pre-drilled anchor points; acetal polymer			
Footnotes		Contact information	
-		Uponor Inc.	
		5925 148th Street West	
		Apple Valley, MN 55124	
		T 800.321.4739	
		F 952.891.2008	
		Uponor Ltd.	
		6510 Kennedy Road	
		Mississauga, ON L5T 2X4	
		T 888.594.7726	
		F 800.638.9517	