Accesorios WIPEX que cumplen con las normas de ASTM

Project information

Job name:	Location:
Engineer:	Fecha de envío:
Contractor:	Presentada por:
Manufacturer's representative:	Approved by:

Technical data

Material	Brass
Subcomponent Material	Body: DZR (dezincification-resistant) brass Clamp ring: DZR brass Bolt: Stainless steel Nut: Stainless steel Washer: Stainless steel
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar) 180 °F (82 °C) at 100 psi (6.9 bar) 200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

Product information and application use

Los accesorios WIPEX se utilizan para todo tipo de aplicaciones de tubos de polietileno reticulado (PEX-a™) de Uponor. Los accesorios de latón resistentes a la deszincificación (DZR) son seguros para el entierro directo en el suelo.

Part name	Part no.	End Type 1	End Type 2
WIPEX Fitting 3" x 2 1/2" NPT	5550030	Compression 3"	MNPT 2-1/2"
WIPEX Fitting 4" x 4" NPT	5550040	Compression 4"	MNPT 4"

Part name	Part no.	Codes	Standards	Listings
Accesorios WIPEX que cumplen con las normas de ASTM	All	IMC|UMC	CSA B137.5|ASTM F877	IAPMO-ES
In addition, the following parts have additional codes, standards, or listings:				
WIPEX Fitting 3" x 2 1/2" NPT	5550030		NSF/ANSI 14	
WIPEX Fitting 4" x 4" NPT	5550040		NSF-14	

Installation

Utilice adaptadores de latón DZR para realizar la transición de los tubos PEX de Uponor a rosca NPT macho. Utilice juntas tóricas de EPDM entre las diferentes partes para el sellado. Para obtener más información, consulte la hoja de instrucciones de accesorios WIPEX de Uponor.

Related applications

Sistemas de tuberías preaisladas

Sistemas de calefacción y refrigeración radiante

Sistemas de Prevención del Permafrost

Sistemas de acondicionamiento de césped

Footnotes

-

Contact information

Uponor Inc.
5925 148th Street West
Apple Valley, MN 55124
T 800.321.4739
F 952.891.2008

Uponor Ltd.
6510 Kennedy Road
Mississauga, ON L5T 2X4
T 888.594.7726
F 800.638.9517

© 2024 Uponor North America. All Rights Reserved